

A WEEKLY JOURNAL OF PRACTICAL INFORMATION, ART, SCIENCE, MECHANICS, CHEMISTRY, AND MANUFACTURES,

Vol. LXXIII.—No. 1.

NEW YORK. JULY 6, 1895

A STEAM SUPPLY FROM COMBINED LOCOMOTIVES.

Some time ago the Obio Steel Company, of Youngswith the boilers already constructed, and not wishing to wait for the completion of those in course of erec-

side at the rear of the engine house, connected them up as shown in our illus. trations.

Each locomotive supplies steam to the extent of 100 horse power, the aggregate being 600 horse power.

Our engravings are from photographs specially taken for the SCIENTIFIC AMERICAN by Mr. James J. Dalzell, of Youngstown. In our SUPPLEMENT of this week we give a num. ber of illustrations of the works of the Ohio Steel Company, which, we believe, is now the second largest establishment of the kind in this country.

Recent Tests of Position Finders.

An interesting series of tests of the position finders of Lieutenant Bradley A. Fiske, U. S. N., and Lieutenant I. N. Lewis, Second Artillery, occurred at Fort Hamilton on Tuesday, June 25, 1895, before mem bers of the board appointed by the Ordnance Department. Broadly speaking, the work of the posi-

ing and are only raised at the moment of firing; and in the mortar batteries, as at Sandy Hook, the mortars are entirely concealed, being below the level of the ground, yet with the aid of position finders, which may be a mile away, it is possible for both the guns and mortars to put 45 per cent of hits on the deck of an imaginary ironclad, at ranges of from 3,000 yards to several miles. The object of the position finder is not only to assist in aiming one gun or a set of guns, but is intended to place within the power of the commanding officer of the fort the con. trol of all of the variously disposed batteries in the tion finder he ascertains the location of a certain group of ships and sees what batteries may be trained upon it. He then telegraphs to the batteries the position and distance he has determined, and they direct their fire accordingly, following the

ships with their own posi-

tion finders. If the guns were not of the disappearing the circuit is balanced; the pointer arm type, they would need only a range finder, as non- a chart representing the area, which includes the town, O., not being able to generate sufficient steam disappearing guns can point directly at the target, position of the distant object on a reduced scale, using the ordinary gun sight. We have described the On this chart there is a simple pivoted arm which can Fishe range and position finders in detail in the SCIEN- be trained directly on the object; the arm may be tion, obtained six locomotives from the N. Y., L. E. & TIPIC AMERICAN SUPPLEMENTS, 788, 769 and 805. In mechanically controlled by a telescope directed upon W. RR. Co.'s round house, and, placing them side by brief, the new position finder may be said to be a the object, so that it will make with the other arm an

A STEAM SUPPLY FROM COMBINED LOCOMOTIVES.

jects both at rest and in motion, and the test under- It embodies, first, a telescope moving over an arc taken by the board consisted in making estimates by of conducting material and which is pointed upon the use of these instruments of the range and direct he distant object; second, a pivoted pointer moving tion of various objects and comparing them with a over a like are of conducting material in a Wheatknown standard. The modern fort does not consist of stone bridge circuit with the first named arc, the a single inclosure, but is rather a series of isolated arrangement being such that when the alidade arm Many of the guns which attached to the telescope on the first are and the

angle equal to that made by the lines of sight drawn from the two telescopes to the object. The position of the object is then shown by the intersection of the electrically directed pointer and the mechanically directed arm upon the chart. The horizontal base line is used in Lieutenant Fiske's instrument and a vertical base line in that of Lieutepant Lewis; the test was in no sense a competitive one, as the conditions under which the two systems are expected to work are very different. The Lewis instrument is available for high elevations and is simpler than the Fiske apparatus. One of the great advantages of the Lewis instrument is that it can be used with a vertical as well as a hori. zontal base, and in that case a 50 foot base would be sufficient.

Two temporary conning towers were erected on the north and south parapets of the fort, from which they commanded the whole lower bay, and in these the Board met for the tests.


tion finder is to plot upon a chart the position of ob- simplification and amplification of the rauge finder. In each tower one of the telescopes of the position finder had been set up. The standard adopted for the purpose of comparison was furnished by a set of triangulating instruments, one of which was at Fort Wadsworth, on the Staten Island side of the Narrows, and the other at Fort Hamilton, the operators being connected by telephone.

Observations were made upon a stationary point, are mounted in these forts and batteries are disappear- pointer on the second are stand at the same angle, the Coney Island lighthouse being used. Other ob-

servations were taken on Hoffman and Swinburne Islands and other points of known distance with excellent results. Then a series of observations were taken on schooners and other passing craft, and afterward compared with ranges taken with a transit. In every case the Fiske position finder showed an error of much less than one per cent for each thousand yards of range, which is the standard required by both the United States and English governments. A series of tests of the Lewis depression position finder was also made with very satisfactory results.

The Electrical Industry.

The electrical industry, according to the Electrical Review, is about 17 years old and employs over \$1,000,000,000 of invested capital. The greater part of this immense investment has been made since 1888, when the electric motor was proved to be a success,



A STEAM SUPPLY FROM COMBINED LOCOMOTIVES.

Scientific American.

ESTABLISHED 1845.

MUNN & CO. Editors and Proprietors. PUBLISHED WEEKLY AT

No. 361 BROADWAY, NEW YORK.

O. D. MUNN.

A. E. BEACH.

The Scientific American Supplement distinct paper from the Scientific American Supplement were rever number contains Bocavo pacca, uniform using weekly. Every number contains Bocavo pacca, uniform using the second of the Bocavo pacca, uniform to the second pacca, uniform to supplement, a second of the Bocavo pacca, uniform using the second pacca of the Bocavo pacca, uniform to the Postal Union. Single copies 10 cents. Sold Inswendedsor throughout the country. See prospectus, last page, seablined Hares.—The Scientific American and Supplement be sent for one year, to one address in U. S. Carada or Mexico, on pt of even dollars. To foreign countries within Postal Union eight re and fifty cents a part.

Building Edition of Scientific American. Hallding Edition of Scientific American.

THE BUILDING EDITION OF THE SCIENTIFIC AMERICAN is a large and plendid illustrated periodical, issued monthly containing floor p and ad perspective views pertaining to modern architecture. Each number illustrated with beautiful plates, showing desirable dwellings, public alidings and architectural work in great variety. To builders and all who antemplate building this work is invaluable. Has the largest circulation f any architectural publication in the world.

Single copies 25 cents. By mail, to any part of the United States, Canada 7 Mexico, El.36 a year. To foreign Postal Union countries, \$6.00 a year. combined rate for BUILDING EDITION, SCIENTIFIC AMERICAN, to one direct, \$6.00 a year. To foreign Postal Union countries, \$6.00 a year. To foreign Postal Union countries, \$6.00 a year.

T. \$3.00 a year. To foreign Postal Union countries, \$11.00 a year.

Export Edition of the "cientific American seek Postal Union countries, \$11.00 a year.

Export Edition of the "cientific American, edition of the Schertfic American, published monthly, and the analytic property with the SCHERTFIC AMERICAN, published monthly, and the analytic property with the SCHERTFIC AMERICAN. Every number of the Schertfic Postal Conference of the Schertfic America, Spain and Spanish postal countries and Schertfic Postal Conference of the Schertfic Postal Conference of the Schertfic America, Spain and Spanish postal Conference of the Spanish language is spoken. The Schertfic American Conference of the Spanish postal places throughout the world. \$10.00 a year, post paid to any seworld. Single copies 5 cents. bo desire to secure foreign trade, may ayed announcements published in this MUNN & CO., Publishers. 361 Broadway, New York.

est way to remit is by postal order, express money order, cheek. Make all remittances payable to order of MUNN Renders are specially requested to notify the publishers in case of ilure, delay, or irregularity in receipt of papers.

NEW YORK, SATURDAY, JULY 6, 1895.

ercentage, determining ctivity of

Hook
Guns, great, the manufacture of
Heavens, the, in July.
Insect, a strange
Inventions, recently patented
Lantern, an astronomical*
Locomotives for steam supply*
Metal and Lund, the
Notes and queries

TABLE OF CONTENTS OF SCIENTIFIC AMERICAN SUPPLEMENT No. 1018.

For the Week Ending July 6, 1895.

Price 10 cents. For sale by all newsdealers. Price 10 cents. For sale by all newsdealers.

FAGE

I. ARBORICULTURE—North American Woods.—A description of a magnificent collection of North American woods belonging to the American Museum of Natural History in Central Park.—The collection was made by Prof. Charles 8. Sargent.

Street Trees.—The subject of beautifying our cities is now receiving great attention, and the present paper gives some valuable information rewarding the plausing of trees in city streets.

II. ARCH (AP)LOGY.—Results of Excavations in the Memphis Necropolis. Daubur, and Lieht.—A description of the very recent excavation by N. G. De M-yrase.

III. BIOCHRAPRIV.—Professor Lobbs? Meyer.—An interesting account of this great chemist by M. M. PATRISON MUIR.—

HEGI IV. BIOLOGY.—Life Without Microbes.—dives results of some interesting appriments.—

10718

V. BOTANY. - A Hybrid Tousco. - A California specimen is illustrated. - I illustration vitation of Secola Article by W. BOTZING HEMSLEY.

VI. CHEMISTEY. Acceptence. By Dr. F. L. SLOUM. An interesting paper on the new Studies and the comparison of its luminosity with methane, ethane, butyless, etc.

On Argon and Helium. An analysis of the gas which was obtained from a meteorite.

Only with methatrs, examine, our reason was recovered to the gas which was obtained from a meteorite.

Terrostrial Beltium (1).—On a gas showing the spectrum of heltura, the reputed cause of De. one of the lines in the spectrum of the sum's chrumosphere. Preliminary notes by Prof. Wa. The continuous of the sum's chrumosphere. Preliminary notes by Prof. Wa. Will. Ev. Clark the continuous of the sum's chrumosphere. Preliminary notes by Prof. Wa. Gasouse Furnary recent locating of the Royal Institution on wateroating and interrupted electric currents.—4 illustrations.

VIII. Ev. CLUTION.—The Descent of Man.—An abstract of researches of Prof. B. D. Copt.—The paper treats of man's original ancestor, the order of succession, man's composite descent, the order of succession, man's composite descent, the Royal Institution of Prof. B. D. Copt.—The paper treats of man's original ancestor, the order of succession, man's composite descent, the Royal Terron (Stretch Staties) in Greenland

Z. M. ATHERATUS.—A New Method of Computing.—By B. W. Schitzvitze, of Yale University.—Illustrations.

Z. M. Stretch Pallon C. Schill world No.—Residence Continus for Iron Stretch.—Fallon C. Schill world No.—Residence Continus for Iron Stretch.—Fallon C. Schill world No.—Residence Continus for Iron Stretch.—Fallon C. Schill world No.—Insulations, adulterants, etc.—By M. P. W. O.D.—The installment treats of natural and artificial asphalt continus; iron oxide paints, sinc and lead oxides, white lead, red M. M. M. P. W. O.D.—The Only Bloom of Company's Plant at Younger.

P. WCOD.—This installment treats of natural and artificial asphalts and any production into ordice paints, sinc and less discles, white lead, red ead, and pyrolusite paints.

METALLORGY.—The Ohio Steel Company's Plant at Youngstown, Ohio.—A description of this large plant, with views of the Seesemer converters, the blowers, force pumps, etc., taken directly from photographs on the spot.—I (Instrations.—The Heduction of the Raren Metals from Their Oxides.—By Prof. W. C. Roberts.—A current.

MISCELLAN ECUE.—The Chilean Hall of Congress.—A description of the Chilean Legislative Palace at Santiago, which has seen totally destroyed by fire.—Il illustration.

NATURAL HUSTOR ALTOR X. BLAX.—From the Proceedings events that John By Table Altor of Collecting and Preserving Flash.—By Table Altor X. S. Bax.—From the Proceedings.

RECENT PROGRESS IN SOIL ANALYSIS,

The usefulness of the chemical analyses of soils in practical agriculture has long been a theme of contention among agronomists. On the one hand the advocates of chemical analysis have contended that the agricultural value of a soil could be easily deduced from the data afforded by analysis. On the other hand, it has been affirmed with equal persistence that the data of a chemical examination afforded no just the sample. It is not the intention here to review these discussions, but it will be sufficient to say that there is a certain relationship between the quantities of plant food revealed by chemical analysis and the productiveness of the soil.

It is so evident, however, that this relationship is not constant that it is not necessary to cite any proof. The physical state of a soil, the elimatic condition prevailing, the character of the cultivation and the nature of the crop have all to be considered and all have their influence. It has long been known that the supply of water which is furnished to the plant has more influence upon the amount of product than the fertility of the soil itself. A given field which will in one season produce a maximum crop will with practically the same amounts of plant food available in the soil in the very next season give a minimum yield. is therefore evident that, without taking into consideration all the conditions above mentioned, no safe prognostication of yield can be based upon chemical data alone

The principles of chemical analysis of a soil have been firmly established and especially in this country chiefly through the researches of Hilgard and Peter. While the methods of examination may vary in unimportant particulars, the general principles of procedure have remained the same for many decades. It is not believed that there can be any very important amendment of a useful nature made to the methods already in use.

The digestion of a soil of a given degree of fineness for a given length of time in hydrochloric acid of such a density as to be practically preserved at a given point of saturation throughout the whole course of solution leaves little to be desired in the way of scientific accuracy in securing the soluble constituents of a soil. On the other hand the processes of bulk analysis are based upon the well known principles of examination of minerals which have been so well established as to have suffered little change during the past few decades, nor is it likely they will suffer any great change in the future.

We must look, therefore, for progress in the line of soil analysis in some other direction than in that which has been so thoroughly investigated in the past.

Among the prominent features of recent investigation may be mentioned two which are of prime importance. In the first place attention is invited to the attempts to imitate in the chemical laboratory more nearly the solvent action of bio-chemical activity upon the plant foods present in the soil.

Every chemist has been struck with the fact that the achievements of blo-chemical activity are far more wonderful in their nature than the most brilliant achievements of the chemical laboratory. We find passing into solution in the juices which circulate through plants substances which are obtained only with the greatest difficulty and at the highest temperatures in the laboratory. We find everywhere in the vegetable world striking instances of metabolism which any chemist, even the most distinguished, would be glad to imitate. We find silicates of the most refractory nature dissolved and in this state passing to form new combinations in various parts of the plant, especially in the bark and the leaves. We find in the same juices the alkalies which only a short time before were united in the most stable chemical compounds in the mineral fragments of the earth's crust. We find compounds of mineral acids broken up, the mineral acids driven out by organic acids which ordinarily would not affect them at all and the bases with which they were combined passing in organic forms into the vegetable organism.

Evidently, therefore, in attempting to imitate in the laboratory these complicated chemical phenomena we should not lose sight of the fact that it is not possible for us to measure by our ordinary methods the power of vegetable metabolism. Nevertheless we are justified in assuming that as a rule boiling concentrated bydrochloric acid will attack mineral fragments in a way different from the organic acids which are brought contact with them by the rootlets of the plants. Acting on this idea, it has been suggested, especially by Dyer, to substitute organic acids or their salts for mineral acids in determining the available quantities of potash and phosphoric acid in soil samples. With this idea in view the chemists belonging to the Association of Official Agricultural Chemists have been during the past year engaged in co-operative work, with a view to testing the merits of these methods of determining solubility.

It is evident, however, that no method of arbitrarily determining the solubility of plant food in soils can

prove of actual value unless it be tested against the actual capabilities of plants acting upon soil of the same description. It is with this end in view that the Department of Agriculture organized a system of soil analysis in which the chemical results obtained in the laboratory are checked against the actual results obtained by experimental growth in pots. These experiments have now been under way for two years, chiefly, however, with the idea of testing the proper processes criterion of the availability of plant foods found in to be employed. This having been, with a certain degree of success, accomplished, the work is now considerably extended. A vegetation house has been built capable of accommodating 200 pots. These pots are kept on trucks running on rails. During the day they are run out into the open air and sunshine; during the night and in time of storms they are kept in the vegetation house, which is covered with glass. The soil which is contained in each of the pots is subjected to chemical examination in various ways and with various solvents. In this way it is believed that the actual available plant food which a soil contains, as shown by the character of the crop grown, will be by some of the methods employed indicated with a considerable accuracy by the chemical analysis.

Another most important step forward in the examination of soils consists in the methods which are now employed for determining the number and vitality of the nitrifying organisms which they contain. As is well known, the nitrogen which plants use as food can only be assimilated after it has been oxidized by passing through a vegetable organism of a lower nature. The process of changing organic nitrogen, which plants cannot assimilate, into nitric acid, which is a food suited to their needs, is called nitrification.

The process of nitrification consists of three distinct steps. In the first place, organic nitrogen is changed into ammonia. This change is produced by a number of organisms existing in the soil, the most active of which is the bacillus mycoides. The ammonia thus formed is next converted into nitrous acid by the action of a genus of organisms-nitrosomonas. The nitrous acid produced as above described is oxidized to nitric acid by another organism, the nitrobacter. But it is not our purpose here to discuss the processes of nitrification, but rather the methods which are to be employed in examining soils for these organisms. It will not be long before a chemical analysis of a soil will not be considered to be complete until the sample has been examined for the number and vitality of the nitrifying organisms which it contains. In order to make such an examination of practical value, the samples of soil must all be taken under such precautions as to exclude any contamination, and the cultures for developing the micro-organisms must all be conducted under the same conditions. In order to secure this uniformity, the Department of Agriculture has developed a method of taking the samples in sterilized tubes, under precautions which render contamination impossible, if the directions are carefully followed. The samples of soil thus obtained are used for seeding culture solutions, and the number and vitality of the nitrifying organisms in each sample can be determined by noting the time at which nitrification begins in each of the solutions, and by the seeding of sub-cultures from the original cultures employed. This work is now going on in our laboratory on samples of typical soils and subsoils taken at the agricultural experiment stations of different States, and representing the same samples that are employed in the pot cultures and for chemical analysis. By proceeding in this way, it is seen that a uniform method of chemical and bacte. rial examinations of the soil is secured, and the data of these examinations are checked directly against the products of vegetation secured in the experimental pots.

Further progress has already been recently made, especially in this country, in the physical analyses of soils, chiefly through the researches of Whitney and King. The separation of a sample of soil into silt particles of different degrees of fineness will give data of great value in respect of the capabilities of a soil for holding moisture and delivering it to the roots of growing plants. All the physical data obtained from the examination are of value in the final judgment, and should be considered in connection with the chemical and bacterial data obtained as above described.

The Seasoning of Stone,

Stone, like lumber, requires seasoning. Stone is often spoken of as the synonym as a rock," we say, but, as a matter of fact, stone is very far from being solid. A cubic foot of the most compact granite, for instance, weighs about 164 pounds, while a cubic foot of iron weighs 464 pounds. This plainly shows that in between the atoms which compose the mass of the most enduring stone there exists much space for air, moisture, etc. This seasoning of stone prior to use for building purposes has been well understood by the architects of all ages, but in the modern rush of nineteenth century building too little attention has been paid to it. Now it enters into the calculations of every good architect.

THE HEAVENS IN JULY.

The splendor of the planetary displays in the evening skies of May and June will never be forgotten by those who, looking out from the shadow of the earth into the realm of sunshine beyond, beheld Jupiter and Mars and Venus and Mercury reflecting the solar glow like a fleet of signaling ships. In exchange for this, July has only the spectacle of the continued brightening of Venus. Mercury, in the constellation Gemini, was overtaken by the sun on the last day of June, after which it became a morning star, and Jupiter, also in Gemini, will become a morning star after July 10. Mars, in Cancer, still remains an evening star, but too near the sun and too much diminished in light to at-

Venus alone continues to gain in brilliance every night. Viewed with a telescope, she now appears in the shape of a half moon. On the morning of the 11th she will attain her greatest apparent distance from the sun, and after that time, as, following her orbit, she begins to swing in between the sun and the earth, her form will gradually change to that of a crescent, which will grow longer and more slender as she gets nearer and nearer into line with our globe and the solar orb. Although, as Venus turns her back to us, the proportionate part of her surface which appears from the earth to lie in the sunshine grows smaller, her continued approach more than compensates for this, and so her brightness rapidly increases. At the middle of the month she will be twice as bright as she was on May 1, and between the beginning and the end of July she will gain more than one-third in brightness. Even then she will not have reached her greatest brilliance; that will occur about two weeks later.

As I remarked in a former article it seems to me that of all the planets belonging to the sun, besides the earth, Venus is the most likely to be now in a suitable condition to nurture living creatures resembling the inhabitants of our globe. The fact that she so nearly resembles the earth in size and mass is one of the strong est à priori reasons for this opinion. There is no planetary function so important in respect to the question of habitability as the force of gravitation. That governs the density of a planet's atmosphere, the circulation of its fluids, the ratio of the size of its inhabitants to the strength of their framework, all the mechanical processes and operations occurring upon its surface, etc. Now on Venus the superficial gravity is about 83 per cent of that on the earth. In other words, a weight of 100 pounds here if removed to Venus would weigh 83 pounds there. So slight a differe would probably produce no serious effect upon the conditions of habitability of Venus for creatures of terrestrial mould. The case is quite different for Mars, where the force of gravitation is only 38 per cent of its force here, and also for Jupiter, where the superficial gravity is 2.64 times as great as on the earth. It is true that judged by this test alone Mercury and Uranus might also be regarded as probably inhabited planets, since on the former the superficial gravity is five-sixths of the earth's, and on the latter nine-tenths, but in the case of those planets other considerations come to the front. Mercury, for instance, would seem to be too near the sun, to say nothing of the great eccentricity of its orbit, while Uranus is too far from the sun, receiving, as it does, surface for surface, only one 368th part of the solar light and heat that the earth gets. On Saturn, too, the force of gravitation would offer no obstacle to the existence of terrestrial forms of life, since it exceeds the earth's force only one-fifth, but there are many reasons for believing that the physical condition of Saturn is very different from that of our globe.

Moreover, Venus bears a striking resemblance to the earth, not merely in the conditions governing the weight of bodies at her surface, but also in the undoubted possession of an atmosphere containing watery vapor, in the similarity of her mean density. and probably in the practically identical period of her axial rotation. Indeed, there are two particulars in which Venus would seem to possess a possible advantage over the earth; the first being that her axis appears to be nearly or quite perpendicular to the plane of her orbit, from which it results that her seasons are uniform-always summer near the equator, always spring in middle latitudes, and always winter in the far north and south-and the second that her orbit is so nearly a circle that her distance from the sun is, for all practical effects upon climate, invariable. The on Venus as on the earth (in the inverse ratio of the pressure. The object of this is to prevent the fiber besquares of their mean distances), but inasmuch as the coming discolored, direct steam having the tendency telescopic appearance of the planet suggests that it is to darken it. deeply shrouded with clouds, the greater degree of light and heat received may, in this case, not be disadvantageous

Everything considered then, it is to be regretted that our knowledge of the surface appearance of Venus should be so limited as it is. Schiaparelli has indicated one way in which the difficulty arising from the blinding brilliance of Venus may be avoided, namely, by studying the planet telescopically in broad day, and has himself set the example. Our best equipped

REDRAWING OF WROUGHT IRON TUBES.

observatories ought to be able to tell us something more about that other earth whose distant beauty just now lends so great a charm to the sunset heavens.

Saturn is following the other planets in an apparent march sunward, and now crosses the meridian during the evening twilight, but it will remain an evening star until the 1st of November, and during July will be fairly well placed for observation. It is in the constellation Virgo, about ten degrees east of the bright star Spica. Its beautiful rings still present a most admirable spectacle for a small telescope.

Uranus remains in Libra, a few degrees in an easterly direction from the star a.

Mercury, which, as already remarked, became a morning star at the end of June, will attain its greatest distance west of the sun on the 29d, about which time it may be seen before sunrise.

The month opens with the moon near first quarter. The moon fulls on the 6th, about half past six o'clock in the evening, when it is situated in Sagittarius, near the "Milk Dipper." It reaches last quarter on the night of the 14th, at 10:30 o'clock, in the eastern part of Pisces, and new moon occurs on the 22d, at 82 minutes after midnight. The moon is in perigee, or nearest the earth, on the morning of the 23d and in apogee on the morning of the 11th. The moon will be near Venus on the evening of the 24th and near Saturn on the evening of the 28th.

The earth is in perihelion, or nearest to the sun, on the 1st, about an hour before midnight. Mars is in perihelion less than three days later, but this means more for Mars than it does for the earth, because the former is no less than 13,000,000 miles nearer the sun at perihelion than at aphelion, while the change of distance for the earth between the corresponding points in its orbit amounts to only 3,000,000 miles.

Possessors of small telescopes will be interested this month in the following among other beautiful ob-

Beta Cygni, the splendid colored double star-light orange and deep blue-situated in the foot of the Northern Cross in the constellation Cygnus. Epsilon Lyra, the celebrated quadruple star near the brilliant Vega. A good 3 inch will easily divide both of the pairs composing the quadruple. The Ring Nebula between the stars Beta and Gamma in Lyra. A 3 inch will show it. 61 Cygni, an easily separated pair of small stars, until recently regarded as the nearest in the northern hemisphere of the heavens; and finally, the gorgeous star fields to be found scattered along the Milky Way, which at 9 P. M. about the middle of the month will be seen starting from Perseus, then just rising in the northeast, and passing in succession through Cassiopeia, Cepheus, Cygnus, Lyra, Aquila, Ophiuchus and Serpens, until, spreading widely as it enters Sagittarius and Scorpio, it disappears behind the horizon in the south. This star-jeweled baldric is the chief adornment of a midsummer's night.

GARRETT P. SERVISS.

Adansonia Fiber in Paper Making.

Adansonia bark is chiefly used for the preparation of strong wrapping papers, cartridges, and emery paper. In point of strength the fibers obtained from it are only surpassed by those from the mulberry bush. Papers made with an addition of adansonia fiber not only possess greater tensile strength, but offer greater resistance to tearing. This is characteristic of such papers in a marked degree, and is due to the long, strong fibers intermingling with the others in the sheet of paper. The fibers under the microscope exhibit so distinctive an appearance that they cannot be easily onfounded with other fibers.

To obtain the fiber from the raw bark on the manufacturing scale, the adansonia is first of all cut into small pieces about an inch or an inch and a half long with an ordinary rag chopper, or by hand with strong knives. If it is desired to bleach the fiber after chemically treating the cut bark, it is necessary to subject the raw stuff to a system of purification to remove knots, etc. For unbleached papers this purification is not necessary beyond the usual dusting. When the material has been cut and dusted, it is placed in a revolving boiler, and there boiled for ten hours or so, according to what is considered necessary, in a caustic sodal lye containing 81/2 per cent of soda in the state of caustic and under a maximum pressure of fifty-five pounds above atmosphere. It is usual, in actual practice, to soak the bark in the lye within the boiler, and intensity of the solar radiation is nearly twice as great to see that it is covered with liquor before raising the

If the fiber is properly boiled, the particles of fiber should easily pass between the fingers when lightly pressed, and feel strong and tough. The pulp should not be allowed to lie long, owing to a species of fermentation setting in which destroys the strength of the fiber. It is usually worked up immediately after being boiled.

long time, owing to the slimy nature of the incrusting the committee.

matter surrounding the fiber stopping up the wire cloth covering the washing drum. brushed at intervals to keep it open. Pure clean water must also be used, and the breaking-in roll should be adjusted to thoroughly open out or brush the fiber only, thus preserving its full length.

The preparation and bleaching of the fiber is very similar to jute and manila and such like raw stuffs. The difficulty of bleaching to a good white color with a reasonable amount of bleaching power is also apparent in practice, and depends largely on the nature of and the care with which the chemical treatment has been carried out in the boiling. The loss in weight which the raw adansonia undergoes varies from 50 to 60 per cent, that is to say, 100 parts of adansonia bark will yield from 40 to 50 parts of paper. Papers made from adansonia fiber alone are not frequently to be met with, the bulk of the fiber being used in conjunction with others in making compound papers. These compound papers possess a strength in proportion to the quantity of adansonia fiber used in their manufacture.—Chem. Tr. Jour.

Electric Distribution of Power from Gas Engines.

Captain Lenevue, of France, has recently made a report upon the power installation at M. Linet's chemical works at Aubervilliers, near Paris. The power is generated by gas engines worked with poor gas and transmitted by electricity throughout the works. The plant is considered a model one of its kind.

The complete generating plant consists of three 80 horse power "Simplex" gas engines, placed side by side and capable of working separately or together, each engine driving a dynamo by a belt through an intermediate shaft, to which is also belted a lighting dynamo and a pump. The shaft is provided with couplers. There are also two steam engines that were used before the gas plant was put in. Each generator is of 56 kilowatts, as is also the lighting dynamo, and about twenty motors of from 4 to 15 kilowatts are placed at convenient points about the works. At present only one of the power generators, the lighting dynamo and six motors are in use. The first two exert a useful effect of 91 per cent at 450 amperes, falling to 75% per cent at 130 amperes. The efficiency of the 18 horse power motors is 89 per cent; of the 9 horse power, 88 per cent; and of the 5 horse power, 86 per cent.

The results of the test of this plant made by Captain Lenevue and the engineer of the works are as follows:

 THE REEL	
Circumference of the pulley on which the frio	
tion brake was mounted	. 21 feet 9 inches.
Diameter of ditto	6 feet 11 inches.
Circumference of brake's action	. 30 feet.
Diameter of ditto	7 feet.
Diameter of cylinder	25 inches.
Piston stroke	
Net total coal consumed	
Duration of trial	4 hours 19 minutes.
Mean speed (per minute)	190,290 revolutions.
Indicated horse power	
Organic yield or useful effect	0.709.
Maximum horse power at the brake	95'81 horse power.
Maximum indicated horse power	194.518 horse power.
Indicated horse power of the small motor, esti-	
mated at	4 horse power.
Indicated horse power of the two motors	
Coal consumed per hour	
Coal consumed per brake horse power hour	
Coal consumed per indicated horse power per	
hour	1.12 pounds,
Coal consumed per indicated horse power per	
hour by the two motors	1:08 pounds.

The Royal Crown of England,

The crown used at the coronation of Queen Victoria in 1838, which is said to be the heaviest and most uncomfortable diadem in Europe, contains 1,278 rose diamonds, 1,363 brilliants, 278 round pearls, four large pendant shaped pearls, one immense ruby, four smaller rubies, one large sapphire, 26 smaller sapphires and 11 emeralds. The large ruby is set in the center of a diamond Maltese cross at the front of the crown. This stone was given to Edward I by Don Pedro the Cruel, and was worn by Henry V at the battle of Agincourt, when it was set in his steel casque. It is peculiarly cut and its center is hollowed out to form a setting for a smaller ruby. Many of the stones were taken from old crowns now unused and others were furnished by the Queen herself. They are placed in settings of both gold and silver and incase a crimson velvet cap with an ermine border. Four imperial arches spring from the four sides and support the mount, which is composed of 438 diamonds, and the whole is surmounted by a diamond cross whose center is a single rose cut sapphire.

It is proposed to include an international exhibition of aeronautical apparatus among the interesting features of the Paris Exposition of 1900. The sub-committee on aerostation in charge of the matter are making preparations for the admission of balloons of all kinds, flying machines and soaring apparatus of every The competition for honors will, it is description. The pulp from the boilers is then washed in the stated, be open to foreigners and French inventors on breaking and washing engine, a process which takes a equal terms. Commandant Renard is at the head of

AN IMPROVED FRUIT JAR CLAMP.

The illustration represents a strong and inexpensive clamp, readily applicable to a fruit jar and cap, and adjustable to make a watertight seal, so that the jar may be held submerged without permitting water to run into it. The clamp has a yielding fastening device which permits any gas or steam that may be gen-




DILWORTH'S FRUIT JAR CLAMP.

erated to escape, but it may be quickly adjusted to bind the cap rigidly in place and make a hermetical seal. The improvement has been patented by Mr. Henry C. Dilworth, of No. 568 Greenwich Street, New York City. The main clamping piece has inturned flanges which fit beneath the rim ordinarily found on fruit jars, the cap resting on the usual gasket, and on the under side of the clamping piece is a flat curved spring, one end of which is fastened to the clamping piece, and there being centrally on the under side of the spring a cushion, to prevent the spring from contacting directly with the cap. In a central slot of the clamping piece is pivoted a locking lever carrying cams adapted to bear centrally upon the spring. In the illustration, Fig. 1 represents the clamp applied to a fruit jar, the cam pressing firmly upon the spring when the locking lever is turned down, and at the same time drawing upon the main clamping piece to firmly lock the cap and make a hermetical seal. In the different positions of the locking lever indicated by the dotted lines and in Figs. 2 and 8, the cams are released from engagement with the spring, and the clamp may be readily slipped on or off the top of the With this adjustment the spring presses down on the cap with sufficient force to prevent water from running into the jar when it is submerged for cooking or other treatment, although the pressure is not so great but that gas or vapor generated may escape without breaking the jar. Patents have also been obtained for this invention in Canada and the principal European countries.

A RIBBON SUBSTITUTE FOR BICYCLE CHAINS.

The advent of the safety bicycle rendered some means of connecting mechanism a necessity; gear wheels, bevel wheels and the chain and sprocket wheel were all tried, and at the present time the latter system appears to be the most popular. The chain, however, has marked disadvantages, such as weight, difficulty of properly cleaning and lubricating, and, lastly, on account of the liability to fracture at one of the many joints. The wire cable, in spite of its light-



A RUBBON SUBSTITUTE FOR RICYCLE CHAINS

ness and strength, has not been applied practically to bicycles on account of the imperfection in the means proposed to assure adherence on the pulleys. The metallic ribbon has several advantages to recommend its ab-it, as its lightness, flexibility, its strength, and its ab-

course, detracted from its strength. These difficulties were obviated by using a special ribbon made from a regular intervals orifices are cut. The sprocket wheel eugages the ribbon with the aid of these holes. The relative size of the wheels is the same as usual. The number of teeth on the sprocket wheel is decreased. The ribbon can be cleaned in a moment. For our engraving and the above particulars we are indebted to the Revue Universelle.

The Electric Bailway in Chicago,

Electric lines now connecting with the business center of Chicago, either completed or under way give a grand total of 500 miles. The benefit of such transportation facilities to a city can hardly be over estimated, for the speed of travel will average nearly eight miles per hour or twice that of horse car lines. Since the opening of some of the new electric lines, a few weeks ago, a great improvement has been noticed and favorably commented upon by nearly every one. In the outer portions of the city, or six, seven and eight miles from the business center, the number of new buildings being erected would lead a person to believe that there was a boom in building. Residence as well as business property has increased noticeably in value.

The operation of the trolley lines is almost perfect, as the cars run smoothly and without delay, there being very few accidents to persons or machinery. About six months from now the city limits in any direction can be reached from the business center by street car lines in about one hour. The benefit to the city on account of the time thus saved will be inestimable. The lines already projected will bring every block within the city limits within easy walking distance from the car lines.-Stationary Engineer.

AN ASTRONOMICAL LANTERN.

With the simple form of lantern shown in the illustration, and easily made small maps or charts of the star groups, a great deal of instruction and entertain-





A LANTERN AID TO STAR OBSERVATION.

ment may be realized. The lantern body may be of tin or wood, with flues to afford the necessary ventilation, and in one side has slideways, to facilitate the placing of the diminutive star charts in position in the side of the lantern. The lantern may be readily carried in the hand, and an illuminated chart thus representing any particular group of stars in the heavens greatly facilitates the finding of the group, furnishing most interesting and very simple star lessons. For the charts or maps, a simple blue print is found quite sufficient, where regularly prepared slides are not obtainable, and such prints may be made from originals prepared by the observer, or copied from any of the numerous publications in which star maps are given.

Paste.

J. H. Baldock, in a discussion on the use of starch as mountant, pointed out that the starch must be brought into a state of disintegration, not solution, the usual plan being to make it into a cream with cold water, and then, while constantly stirring, pour ater until thickening tak complete disintegration is obtained, however, by subsequently boiling for a few minutes, while a clearer jelly is obtained, and better keeping properties are secured. The paste should not be too thick, and if not made fresh at the time of using, should be boiled in starch paste for photographic purposes. H. D. of the car may shoot at would-be train robbers. sence of joints. As with the wire cable, it was found heating, with constant stirring, until thickening with the use of an alu that it was very difficult to secure good adhesion on occurred. Heat for a few minutes longer, remove be carried by four men.

the pulleys unless the ribbon was very taut, which, of from the source of heat, add half an ounce of glycerin and, when nearly cold, half an ounce of methylated spirit. A few drops of oil of cloves or other essential steel analogous to that used in piano wire, and at oil may be added if desired, but this is not necessary.-Photography.

A DOUBLE BOTARY TOY WINDMILL.

The attractive toy for children represented in the illustration has been patented by Mr. Frederick Beaumont, Jr., of No. 1307 Franklin Street, Kansas City, It has two wheels, one inside the other, which



BEAUMONT'S TOY WINDMILL.

revolve in opposite directions at the same time. The small figure is a side view of the device. The wheels and vane may be of wood, tin, paper, celluloid, etc., and in bright colors, and the vane presents obvious advantages for use for advertising purposes.

A BULLETPROOF DOOR AND WINDOW SHIELD FOR MAIL AND EXPRESS CARS.

This improvement, for preventing the felonious entrance of train robbers to mail and express cars, has been patented by Mr. Charles G. Ingalls, of Waucedah, Mich. It consists of a two-part shield of plate metal, shown applied and in lowered position over a car door in Fig. 1, while Fig. 2 is a sectional view representing the shields for opposite doors folded up on the roof of the car. The upper section is strongly hinged to the side of the car body, the hinges having their joints connected by a single pintle rod around which is a coiled spring, to aid the quick descent of the shield when required. The side edges of both sections are flanged and tapered, a flange on the lower edge of the lower section joining the side flanges, and the lower section having an overlapping contact with the adjacent portions of the upper section, there being duplicate spring-jointed connections between the lapped portions of the sections. There are pivotal connections between the lapped portions of the shield sections, which are retained in close contact when the shield is lowered by spring latch hooks. The shields are held in their folded position on the car roof, with the lower section imposed on the upper section, by detent hooks and a locking mechanism arranged to permit the simultaneous release of both sections upon the pulling of a cord or band which hangs pendent in the car, the shields being then instantly thrown into a depending



INGALLS CAR PROTECTOR.

well, and have a little borie or salicylic acid or oil of and locked position, as shown in Fig. 1. In each of cloves added as a preservative. Alum is objectionable the shields are perforations through which occupants

> EXPERIMENTS are being made in the German army with the use of an aluminum pontoon. It can easily

REDRAWING OF WROUGHT IRON TURES.

Redrawn wrought iron pipes or tubes are old stock that has been collected up, reheated and drawn through circular steel dies which press the tubes into the right diameter. This stock, which consists of old boiler tubing, railings, etc., is first heated red hot in a furnace. The furnace has two ovens or fire boxes about 8 inches in height and lined with fire brick. These fire boxes also heat the boiler, which is incased the center or oval part being about 3 inches thick. in the brickwork above. In one of the ovens a numthe hot tubes come in contact with the water the dirt end of the tube firmly. A movable hook attached to

the carriage is an endless chain 45 feet in length. This chain is connected to the machinery and travels at the rate of about 80 feet per minute, running over a number of spiked 10 inch pulleys connected to the draw bench underneath. The dies are about 8 inches in diameter on the outside. The inside diameter where the each 15 feet in length, about 18 inches in width and pipe runs through ranges from 1 to 6 inches. The flanges on the dies are about 1 inch in thickness

When the heated tube is ready, an attendant place ber of the old tubes are heated, the attendant, as soon the flat side of the die against the head block. The as they become red hot, removing them by means of tube is then drawn out of the furnace with a pair of tongs and placing them in a dipping tank or reservoir tongs and the flanged end cooled with water. The containing cold water. This reservoir is about 18 end is then run through the die into the jaws on the inches in width and 24 inches in depth. As soon as pulling carriage, which, when drawn taut, grips the

end of the carriage is then dropped down into a link of the chain and the apparatus set in motion. As the chain moves, the carriage is forced

center of the draw bench and between the wheels of The pipe is placed in the machine and the knife or cutter put in position. The machine is then set in motion and the knife forced against the revolving pipe, which makes about from 25 to 40 revolutions per minute, according to the size of the tube, and is cut through in about two minutes. The knives are made of steel about 4 inches in length, about 1 inch in width and about 16 of an inch in thickness


The machine will cut from 25 to 80 pipes per hour. During the cutting operation softsoap is applied, which keeps the knife from getting heated and also makes the material cut easier. The pipes when finished are used principally for boilers, green houses,

hot water purposes, railings, paper rollers, etc. The sketches were taken from the plant of the Eagle Tube Company, Jersey City, N. J.

New Method for Determining the Percentage of Alcohol.

J. Barker - Smith (Jour. de Pharm. d'Anvers, li, 1895, p. 121) recommends a method depending on the well-known fact that alcohol and alcoholic liquids

water. He employs one drachm each of the liquid to be examined and of water, both at the same temperature, and mixes them quickly in a cylindrical receptacle; the latter should be provided with a cork and should not be touched by the fingers. The temperature of this mixture is now taken. and by referring to a table showing the temperatures obtained by mixing the same quantity of water with alcoholic liquids of known strength, the percentage of alcohol of the liquid in question can readily be ascertained. This thermometric method would not do where very exact measurements are wanted, for it is not sensitive to less than about 5 per cent of alcohol. It



THE TUBE REDRAWING INDUSTRY.

hammering the heated end to a point on an anvil. less in diameter. This operation is repeated, using The object of shanking is to have a good strong end every time a smaller die until the right size tube has for the jaws on the pulling carriage to catch hold of been obtained. About 1,500 feet of tubing is redrawn ould break off. After shanking the tubes are placed in the other fire box on the straightening table, over which slightly inclined of the furnace and heated up to a white heat, about is a movable flat iron frame which moves back and forth 1,500° F. Running from the mouth of the furnace is when the machine is in motion over the pipe. This a draw bench about 21 feet in length and 10 inches in frame, which is about 5 feet in length and 21/2 feet in

When cool they are shanked by the die. The pipe, as soon as it is passed through the eation is finished the red bot tube is placed

and scale instantly drop off, giving the pipe a brand | the hook, drawing with it the red hot pipe through | would, therefore, not answer for testing wines containing 10 per cent or less of alcohol. One point heating one end of the tube red hot in a furnace, then die, is reheated and drawn through another die a little raised in its favor is that substances in solution do not interfere much with the test.

The above is a convenient and rapid process for determining the alcoholic strength of liquids conwhen the tube is drawn through the die. If the pipe per day, it requiring the labor of three men. After the taining a large percentage of alcohol, such as whiskies, brandies, tinetures, fluid extracts -Merck's.

Good for Peary.

The past winter in Greenland was unusually mild, width. On this bench, traveling back and forth on a width, makes an 18 inch stroke. The weight of the and the climatic conditions have favored Mr. Peary's track, is a pulling carriage, connected to the front end frame, which is about 1,000 pounds, straightens the expedition. The barks Silicon and Salina, the first of of which are two movable steel jaws 8 inches in length pipe in about one minute. After straightening, the the fleet of cryolite traders to arrive at Philadelphia and 11/2 inches in width. At the head of the draw tubes are carefully examined to see that there are no from Ivigtut, report that the Greenland coast has not bench is an iron head block, against which the circu-lar steel dies are held in position. Passing along the the examiner, who then passes them to the cutter, the aurora made the long winter night almost like day.

Colored Fires.

Usually at this season of the year there are calls for colored fires; the following from Merck's Report, which it says are approved formulas, may be of interest. On account of the poisonous and explosive nature of some of the ingredients, the utmost care in their manipulation is necessary,

	BLUE.	
		Paris.
2.	Realgar	. 9
	Charcoal	. 8
	Potassium chlorate	. 5
	Salphur	
	Calcium nitrate	77
OF:	the state of the s	
		Parts.
2	Orpiment	1
	Charcoal	1
	Black antimony sulphide	16
	Potassium nitrate	48
	Sulphur	64

The objection to almost all blue fires is that when burned they generate arsenical fumes, and are, therefore, not suitable for indoor use. A blue which can be

used in a theater or large hall, though less	brilliant
than the foregoing, may be made as follows:	
	Paris.
A. Salphur	15
Potassium sulphate	
Ammon, copper miphate	000
Polamium nitrate	0000
Potamium chlorain,	
A CHILDREN CHICAGO CO. CO. CO. CO. CO. CO. CO. CO. CO. CO	
CRIMBON,	
Canada	Parts.
4. Potassiam chlorate	17
Charcoal	33
Sniphur	90
Strontlam nitrate	270
07:	
	Paris.
B. Charcoal	18
Antimony sulphide	
Potassium chlorate	
Salphur	
Strontlum nitrate	
GREEN.	
C. Shake day Alamah	19
6. Potassium chlorate	
Barium nitrate	
Sulphur	21
or:	
	Parts.
7 Metallic amenie	
Charcoal	
Potasefum chiorate	0
Bulphur	13
Barium nitrate	77
or:	
The last of the la	Parts.
8. Charcoal	
Black antimony sulphide	2

	Strontfam nitrate	290
	Commission and Commission of the Commission of t	_
	GREEN.	
	Potassigm chlorais	. 13
-	Barlum nitraio.	
	Sulphur	
or:		-
O		Parts.
7	Metallic amenie	2
	Charcoal	
	Potaerium chiorato	- 8
	Bulphur	
	Barium nitrate	77
or:		
		Parts.
8.	Charcoal	2
	Black antimony sulphide	
	Potassium chiorate	
	Sulphur	
	Barium nitrate	. 80

	LILAC	Parts.
0	Black copper oxide	gara.
-	Chalk (dry)	
	Sulphur	=
	Putaralum chlorate	40
	PINK.	
		Parts.
TO.	Charroal	1
	Chalk	20
	Potassium chlorate	20 27
	Potaesium nitrato	382
07:		-
		Parts.
11.	Salpher	16
	Calcium chlorido, óriod	28
	Potamium chlorido	61
	PURPLE.	
	PURPLE	Ports.
20.	Lampblack	1
	Realgar	1
	Potaesium nitrate	1
	Balphar	2
	Potaerium chlorate	5
	Strontiam nitrate, fund	16
07:		
		Parts.
300	Copper snlphate	30
	Sulphur.	50
	Potamium chlorate	270
	RED.	
		Parts.
14.	Charcoal	1
	Black antimony sulphide	4
	Potassium chicrate	5
	Sulphur	18
	Strentium nitrate, dried	40
07:		
-		Parts.
18.	Sulphur	16
	Strontiam corbonate	203
600.0	Potantium chlorate	61
or:		
9.0	Antimony sulphide	Paris.
200	Polassium chlorate	8

Potandum chlorate.....

Sulphur.....
Strontium nitrata, fused.....

A little charcoal or lampblack makes it burn quicker.

	VIOLET.	-
		Paris.
17	. Charcoal	8
	Suphur	10
	Metallic copper	25
	Potassium chiornie,	30
or:		Parts.
18.	Alum	8
-	Potaestum carbonaie	3
	Sulphur	4
1	Potantum chlorate	15
	WHITE.	
		Parts.
19.	Potassium nitrate	30
	Sulphur	10
	Black antimony sulphide	5
	Meal powder	8
	Powdered camphor	2
or:		Parta.
90	White amenic	1
300.		9
	Charcoal	
	Rjack antimony	26
	Potassium nitrate	48
	Sulphur	64
	YELLOW.	
		Parts.
91.	Polassium nitrate	3
	Sulphur	4
	Sodjum nitrate	90
	Lampblack	1
or;		
		Partie.
99.	Sodium nitrate	8
	Potassium chlorate	1
	Sheller	1

In the preparation of colored fires the ingredients, which should be perfectly dry, must be separately powdered and sifted through a hair sieve, and put into well stoppered, wide mouthed bottles until ready for mixing. The mortar must be thoroughly cleaned, before and after powdering each ingredient, particularly potassium chlorate. Mix with the hands or with a wooden spatula on sheets of white paper.

Sulphur, and salts of the poisonous metals-antimony, arsenie, mercury, etc.-should not be used in making colored fires for indoor use. The sulphur may advantageously be replaced by shellac, which hardly mokes at all when ignited.

emo	nee at an when ignited.	
EV	or red the following formulas are used:	
2.	or red the redowning formanie are diseas	Parts.
28.	Potassium chlorate	1
	Shellac	1
	Strontium nitrate	. 3
OF:		-
	The transport of the second se	Paris.
24.	Strontium nitrate	12
	Potassium chlorais	8
	Milk sugar	1
	Stearin	2
F	or green the following is employed:	
-	and the same of th	Paris.
25.	Potassium chlorate	2
	Barium nitrate	1
	Milk sugar	1

High Speed of Electric Motors

Some interesting trials on the Nantasket branch of the New York, New Haven & Hartford Railroad occurred June 20 and June 22. The Nantasket Beach branch was chosen for the experiment for the reason that within its limits will be included most of the different problems which will have to be determined to make electricity a successful substitute for steam. The curves are many and sharp, the grades are steep and trains will be run with great frequency. Seven miles is the distance between the Old Colony station and Pemberton. The tracks are fifteen feet apart from center to center, and between the tracks is a single line of poles on which are supported the cables and trolley wire. Upon the tangents the poles are set with such geometrical precision as to secure absolute-ly perfect alignment. The two flexible copper bonds seven inches long are under the base of the rail at each joint and riveted to each rail. A power house, No. 1, is situated midway between the terminals and contains two tandem compound engines; the two generators develop fifteen hundred horse power each. Four motor cars have been built after the style of baggage cars. To secure traction they have been made extra heavy, so that when fully equipped they will weigh about 60,000 pounds each. Two will have four motors each and the other two motors each hung on trucks. The cars are equipped with the Westinghouse air brake, and in addition to a 15 inch gong, there will be a chime whistle worked by compressed air. The test was held in the presence of only a few invite There was none of the gradual increase of speed charthe ease of starting and the speed obtained showed easily drawn. A speed of more than 50 miles an hour timated that the train made at times the enormous "controller" in the motor, so if the additional current times the space of steel.

had been applied, it is thought that a speed of 90 miles an hour might have been obtained on the level

The New Atlantic Steamer St. Louis.

The St. Louis finished her second voyage at New York on June 22, 1895, completing the passage from Southampton in seven days, seven hours and eleven minutes. The outward passage was made in seven days, three hours and fifty-three minutes. When three days out from Southampton, while proceeding in the face of a heavy wind, the ship would not respond to her rudder. An inspection was quickly made of the machinery, which was found to be working perfectly. The hand steering apparatus had been used, and that was tested, but the St. Louis would not respond; a sailor was sent over the stern to see what was the trouble. He discovered at a glance that the bracing plates of the twenty-seven ton rudder had broken and that the fracture extended diagonally upward from the pintle of the rudder; there was therefore no leverage for the steering gear and the ship was practically helpless as far as her rudder was concerned. The captain and chief engineer decided that the twin screws should be used to guide the vessel, so they shifted the action of the port and starboard engine as the course demanded and the St. Louis forged ahead with little diminished speed. The accident was due to a hidden flaw in the steel of which the rudder was made. The rudder was taken off when she reached her dock and that of her sister ship, the St. Paul, was substituted, the work be ing quickly done, and the St. Louis sailed on her third voyage on her schedule time, June 26.

The Strangest Insect in the World.

The aweto, as the Maoris or natives of New Zealand call it, or Hipialis virescens, as naturalists term it, is found in New Zealand, and is a vegetable caterpillar of from three to four inches in length, and, so far, science has not been able to say whether it is a vegetable or an insect. It is always found at the foot of large myrtle trees that have beautiful red flowers on their stems, and a beautiful creeping clematis as white as the snow. The Maoris call this tree by the name of rata. The aweto buries itself among the roots of the rata, a few inches below the ground, and there lives until it is full grown, when it undergoes a most wonderful change. The spore of a vegetable fungus, termed by naturalists Sophoria robertsii, fastens itself to the neck of the caterpillar, just between the head and the first ring, and then grows upward to the height of from six to eight inches. Many people assert that there is never more than one stem, but such is not the case, for some have been found with two stems, although very rarely. The stem shoots up out of the ground, above where the caterpillar is living, about two or three inches; below the earth it grows into the aweto, until it fills up every possible space within the outer skin without changing the form of the insect in the slightest way whatsoever, but simply substituting a vegetable matter for animal matter. As soon as this takes place both the plant and the caterpillar become dry and hard and die, but retain exactly the same form as when alive. The whole has a brown color, and the insect appears a wooden caterpillar, with a huge horn standing up from the back of its neck. How the caterpillar manages to propagate its species no one can tell. Usually the caterpillar becomes a chrysalis, the chrysalis changes into a moth, the moth lays eggs, and these eggs again become eaterpillars, and so on without stopping. Many reasons are given why the plant shoots up from the back of the neck of the aweto. One is that the aweto has a slimy substance oozing from its neck, which, while the aweto is boring at the foot of the rata tree for its only food, catches the seed of the fungus and holds it fast there till the latter begins to grow. When it has sucked all the vegetable life out of the aweto it must naturally die, for it finds no further nourishment. The aweto is often found in large numbers.—Public Opinion.

Relative Strength of Metal and Timber.

Doctor Robert H. Thurston, in a recent article, discusses various materials in which comparisons of interest are made. At the outset he gives the following generally accepted figures: Cast iron weighs 444 pounds to the cubic foot and a 1 inch square bar will sustain a weight of 16,500 pounds; bronze, weight 525 pounds, 50,000; hard "struck" steel, weight 400, tenacity 78,acteristic of the steam locomotive. A test was made 000; aluminum, weight 168, tenacity 26,000. We are of a load of 175 tons, equal to a train of seven cars, but accustomed to think of metals being stronger than wood, and so they are, generally speaking, if only that a load of three or four times as great could be pieces of the same size be tested. But let equal weights of the two materials be compared, and it will was obtained, and for a part of the distance it was es- then be found that several varieties of wood will prove stouter than ordinary steel. A bar of pine just as speed of 80 miles per hour. A hot box prevented a heavy as a bar of steel an inch square will hold up greater increase of speed. When the train was making 125,000 pounds, the best ash 175,000 and some hemlock 80 miles an hour there were still five notches left in the 200,000 pounds. Wood is bulky. It occupies 10 or 12

Correspondence.

A Petrified Tree.

To the Editor of the SCIENTIFIC AMERICAN:

I thought it might be of interest to inform you of the discovery of a petrified tree 165 feet under ground, at the Stolls City mines, eight miles west of this place. The tree was found under 100 feet of lead and zine ores and 65 feet of flint rock. The petrifaction is the best I ever saw. The grain seems to be of a fine wood. Some think it mahogany, others walnut.

H. G. VOORHIES.

Mt. Vernon, Mo., June 17, 1895.

The Uncultivated Bast Fibers of the United

As the indigenous or uncultivated species of plants producing bast fiber in the United States form an interesting group in the fiber series, and are the subject of constant inquiry, a report upon them by Mr. Chas. Richards Dodge has recently been published by authority of the Secretary of Agriculture and distributed by the department.

For the most part, the species considered belong to three large families of plants: the Malvacem, of which the cotton plant is a member; the Asclepiadacee, and the Leguminose. The malvaceous species are the most numerous and possibly the most widely distributed, their fiber possessing fair strength and comparing with jute rather than with flax and hemp, though whiter in color than the former. These Mr. Dodge would consider as jute substitutes, while the species belonging to the two other families, and which yield stronger fiber, may be termed hemp substitutes. and are therefore more valuable.

That these fibers are not employed commercially is due to several causes, one of the principal of which is the want of a satisfactory decorticating machine.

The first of the malvaceous fiber plants mentioned in the report is the swamp rose mallow (Hibiscus moschentos), one of the commonest of mallows and found In many parts of the temperate United States. Experiments with this plant date back many years, and fifteen years ago it was the subject of renewed experiment in New Jersey, the advent of new machinery for cleaning bast calling attention to the plant and placing its cultivation for fiber among the possibilities. Samples of fiber from the New Jersey experiments were considered not only as good as India jute, but as good as secondary grades of imported hemps.

The plant that furnishes the "rozelle" hemp of the Madras territories belongs to the same genus with the above. It thrives in cultivation in Florida, will grow on quite poor land, but will not stand much frost. Scientifically, it is known as Hibiscus sabdariffa

Another malvaceous plant, which grows wild all over India, and which is common in Florida, is Urena lobata. The natives of India consider its fiber useful for manufacture into bagging and twine, and it is regarded as a tolerable substitute for hemp. The fiber is described as very fine and strong, white in color, and a meter in length.

Sida is still another genus of malvaceous plants whose bast is rich in fiber, that of S. rhombifolia being known as Queensland hemp. This species, the fiber of which is said to be easy of extraction and fine and strong, abounds in many portions of South America, and has been known as a weed throughout South Carolina for many years. Mr. Dodge's conclusions regarding the cultivation of the plant on American soil (based upon the results of limited experiment, however) lead him to think that the plant is of too slow growth and the stalks too small when grown to make it of commercial value as a fiber plant.

The cotton plant of Southern agriculture (Gossypium herbaceum) also belongs to the Malvaceæ, and it may not be generally known that its stalks contain fiber of good quality. In the collection of fibers sent to the Paris Exposition of 1889 there was a fine example of the fiber of the cotton stalk, from a plant grown in Georgia, prepared by the American Consolidated Fiber Company from a green stalk sixty days from date of planting. In the letter of transmittal it was stated that "the fiber is not only good for thread, but for a thousand other purposes. It is a splendid fiber for paper also, as it will not tear as easily as that made from wood pulp or rags.'

The okra (Abelmoschus esculentus) has long been regarded as a fiber plant of value in India and other countries, though the production of its fiber has never assumed commercial importance. The plant is a native times in the Southern States for it pods, which form a useful article in the domestic economy. A few years ago okra attracted considerable attention as a possible fiber for Southern cultivation, and a large correspond- line or twine, as roughly prepared. Among the manuence with the department resulted. As is frequently the case, however, the value of the plant and the case of its cultivation for fiber were very much overstated, and subsequent experiments did not substantiate the claims made for the plant. " From a careful consideration of the subject in all its details, not only as relates tivated bast fibers, it remains to mention a few forms a large amount of ash removed.

to our own, but to other countries, and considering the weakness of the fiber compared with jute, I conclude," says Mr. Dodge, "that the cultivation of the okra plant for its fiber cannot be made a paying industry in the United States,"

A very common malvaceous plant that has been cultivated experimentally in the United States, where it is everywhere common as a weed, is the Indian mallow (Abutilon avicenne). The fiber of this plant is known in South American countries as cañapiña. Its Chinese name is ch'ing ma, and it has been exported to England under the common name of jute. It has been called also Abutilon jute, and the name American jute was once applied to it in this country. The plant produces an abundance of fiber, which is strong, glossy, and white, and the ligneous body gives more cellulose for paper stock than any other species. The fiber takes dye readily, and an advantage is claimed in this respect over Indian jute, which is antagonistic to cheap bleaching and dyeing. The fiber was once classified in value between Italian and Manila hemp, but it will not grade so high, it coming nearer to jute, as is proved by its being sold as a variety thereof.

The milkweed family, the Asclepiadaceæ, contains a large number of fiber-producing plants found in various parts of the world. The several species found in the United States all possess a fibrous bark, and bear seed pods filled with silky hairs resembling thistle

The most important species, viewed as a fiber plant, is Asclepias incarnata, or swamp milkweed, which abounds from Maine to Minnesota and southward to Louisiana. The fiber of this plant was well known to our Indians, who used it for making bow strings

Samples of fiber from the plant having been submitted to the department were found to be light gray in color, much finer than hemp as usually prepared, soft and glossy, and of greater strength than the majority of bast fibers of wild growth in the United States

Mr. Dodge thinks that the plant promises better re sults than any of the indigenous species above considered. If it will thrive upon waste lands where no other crops will grow, as it is said that it will, it has to that extent an advantage over hemp, considering the strength of the fiber to be fully equal to that of the lat-As to the value of the fiber in manufacture, Mr. Dodge can make no positive statements further than that samples of binding twine examined were found to be strong and good. As the fiber resembles hemp, there is little doubt that it could be employed in all uses to which the latter may be applied.

The commonest and best known species of milkweed is the Asclepias cornuti, which is found in Canada, grows over a wide section of the United States, and is well known in portions of South America and the Old World. The culture of the plant is said to be attended with little difficulty, as it generally thrives on poor soil, and, like the former species, is perennial. The only portion of it of which practical use can be made is the bast, which furnishes quite a long, glossy fiber that is strong and durable. Early authorities have given this fiber a place between flax and hemp, and it has been claimed that the yield is about equal to the pliant and is said to make excellent horse collars latter.

Dr. Masters states that "its excellent fiber is woven into muslins, and in some parts of India is made into

The fiber forms a good paper material and, doubtless, might be cultivated with profit for this purpose if for no other.

A French firm has used the silk-like filaments of the seed vessels by mixing 20 per cent of the material with 80 per cent of wool, the fabric being called "silver cloth." The substance could not be used alone, as the cells are so smooth that they have no felting property, and therefore will not hold together and cannot be spun. They possess little strength, and can be considered only as "down," useful for no purpose but wadding or for stuffing pillows.

The family Leguminose contains many species of plants that yield a strong bast fiber, some of the foreign species having a known commercial value. In our own country, the single genius Sesbania of this family has attracted attention as a fiber producer. Specimens of the straight stiff canes of S. macrocarpa, or wild hemp of the Colorado River region, have been sent to the department at different times in the past twenty years. The fiber of the department museum sample is three or four feet long. The filaments as extracted are exceedingly coarse and resemble flat ribbons of fiber, uncommonly white and lustrous, and clear and smooth to a remarkable degree. Single filaments are quite strong, of the West Indies, but has been cultivated from early but when several are twisted together they lose part of their strength, a defect sometimes observed in better fibers. The fiber is sufficiently strong for small cordage for ordinary use, though too coarse for fish factures for which it has been claimed that it is fitted are wrapping, writing, and bond papers, twine and cordage, sacking, overall stuff, and Irish linens. The Indians of the West work it into nets and fish lines.

Having noticed the more important species of uncul-

of less importance that have been the subject of occasional inquiry or of limited experiment.

The Indian hemp (Apocynum cannabinum) has from early times been regarded as a useful fiber plant by certain tribes of our Indians, who manufacture from it bags, mats, baskets, belts, twine, fish lines, and nets. The fiber is easily separated from the stalk, and, when cleaned, is quite fine, long and tenacious. In color it is light cinnamon, though finely prepared specimens are creamy white and remarkably fine and soft. The fiber will rank with that of Asclepias for strength, and is readily obtained, since the stems are long, straight, smooth and slender. Although paper has not been made of it, it could doubtless be used for that pur-

Urtica gracilis, one of the stinging nettles, abounding throughout the United States and Canada, possesses a good fiber in its bast. A few years ago it attracted attention in Minnesota, and an attempt was made to reduce the fiber, but the experiment was interrupted before completion and no report could be made.

Another of the nettles, Laportea canadensis, produces an average quality of fiber, samples of which were received by the department from Kansas in 1890. Several years ago the stalks of the common burdock (Arctium lappa) were the subject of experiment in Illinois, with the object in view of producing a fiber material suitable for binding twine. The fibers in the samples submitted to the department were found to be harsh and wiry, very brittle, and to possess little strength. Fiber plants of this class have no value in the industrial economy, the fibrous material in their bast being too inferior ever to be used in manufacture where so many other better fibers are obtainable, and possibly at less cost.

Another form of fibrous material that has been employed to a certain extent in the coarsest of manufactures are the tree basts, or the fibrous inner bark of such trees as the linden and cypress. The linden trees are familiar in our public parks and gardens, where they are cultivated for adornment, though as lumber they are known as basswood. Tilia americana is the American species, while T. europæa is that of the Old World. The inner bark of the former is not utilized, as far as Mr. Dodge is aware, although the bast of the latter is much employed in Russia in the manufacture of an exceedingly coarse kind of rope for making the matted shoes worn by the peasants, and also for the manufacture of the mats which are used to a considerable extent by furniture dealers for packing. American species was the wigobimizh, or "tying bark tree," of the Algonkin Indians, who used the bast for making ropes, thread, and coarse cloth.

The Southern cypress, Cupressus thyoides, has a very tenacious inner bark that can be readily peeled in long strips. It is not likely to come into use industrially in this country, although worthy of notice.

The wahoo (Ulmus alata) is an elm that abounds in the hummock lands of middle Georgia. The bark is very tough, and, when stripped from the tree and steeped in water for several weeks, becomes quite

Finally, the leather wood (Direa palustris), of rich, damp woods from New Brunswick to Minnesota and Missouri and south to the Gulf, has a fibrous bark which is remarkably tough and which was used by the Indians for thongs and by country people for ropes, whence the popular names of leather wood and rope bark.

The Bicycle Hump.

"This protestation against the 'bicycle hump,'" said an old rider to me, "is very funny. As a matter of fact the man who bends over is not 'humped,' but the fellow who undertakes to sit up straight is round shouldered,"

"Watch a rider coming head on," he continued, and you will think the one leaning over the bars is 'humped,' while the other class appears straight. But when they pass and you get the rear view you find the back of the stooped fellow is straight, the bend being at the hips, the shoulders being pushed back square by the weight resting on the rider's hand, resting on top of the bar.

"The rider who tries to sit straight reaches under the grips and by pulling draws his shoulders together, cramping his chest."

I looked for myself and found the statement of my friend to be true. Look for yourselves: you will be surprised.—Bicycling World.

On the railway bridge of the Chicago & Northwestern Railroad in Milwaukee, Wis., a gas engine has been installed by Mr. E. C. Carter, principal assistant engineer of the road, to operate the draw bridge. It performs its work in a most satisfactory manner, and it would appear that this kind of power is particularly adapted for such work. It is cleaner than a steam engine and the fuel is obtained by simply piping city gas to the central pier of the bridge, while with a steam engine coal must be delivered on the bridge and BELICS OF A CUBAN INSURRECTION.

A recent number of La Ilustracion Española y Americana contains a number of engravings of scenes in the vicinity of Manzanillo, which is in the eastern part of the island of Cuba, and the scene of the pres-It was in this part of the island that ent hostilities. the former revolution of 1868 took place. During the fighting which then occurred, the Spanish troops burned down the buildings pertaining to a large sugar estate known as the Ingenio de la Demajagua. Among the ruins left upon the ground was a large gear wheel and a fly wheel. These are shown in our en-graving as they now appear after a lapse of twentyfive years, during which time a jaguey tree has sprung up between the spokes of the gear wheel and has assumed the large proportions represented in our engraving. The growth of this tree gives some idea of buoys on either side of the channel, forming a lighted invention of the builders of the engine. The proporthe Cuban flora and the rapidity with which it springs avenue for the shipping. The lamps are mounted on tions of the multiple cylinder system are those derived

up and spreads over the ground. According to our contemporary, the present uprising of the Cubans is making extensive progress. A large portion of the eastern section of the island is already in the hands of the revolutionists, and it is doubtful whether the Spanish government will be able to bring in troops enough to overcome the patriots.

Brine for Removing Snow and lee from Balls.

The repeated demands by managers for a brine in place of salt resulted in President Fitch, of the Bay City, Mich., trolley road, making a series of experiments covering many months and which were at last successful in producing cheaply a method of compounding a bighly concentrated clear salt liquor with specific gravity greatly in excess of water, and which is absolutely free from deposit or sediment, is no more expensive in first cost than salt, but can be applied with less trouble and expense, and is very much more economical in use, wastage being almost wholly saved. The basis of the triple chlorides, as President Fitch names the liquid, is natural salt water as pumped from his salt wells, with a mechanical and chemical treatment. It will not freeze even at 20" below zero and has an immediate action when applied, its penetrating effects being very much greater than dry salt or the brine formed from salt melting on track.

During the past winter the triple chlorides was used on several street railways with surprising and highly gratifying success, and these roads are so thoroughly convinced of its superior advantages they have abandoned salt

will at once suggest itself to every manager. curves, crossings and switches the brine is applied by the man whose duty it is to sweep these points, pouring the brine from a common sprinkling can with a drawn copper wires. This cable carries successfully, small spout nove just as he uses water in summer.

For main line tracks a small tank or keg can be set on the front platform and the brine fed to the rail by small iron pipes passing through the platform floor and reaching almost to the rails and discharging a stream from the size of a slate pencil up to any amount very bad track and long distances, the sprinkling car used during the summer is pressed into service, the sprinkler being removed or changed so as to dischange only upon the rails. The brine has less corroding makers as an improvement on wood.

effect on iron and copper bonds than salt, and the method will readily commend itself to managers.

Electric Lighted Buoys in New York Bay.

Incandescent electric lamps on spar buoys have been experimentally used in New York Bay for several years, but an installation has now been completed which marks a considerable advance in maritime engineering and renders the entrance to New York Harbor possible for the largest vessels at any hour of the night. Gedney's Channel, which is the course taken by the transatlantic steamers, is only 1,000 feet wide, and while buoyed by day, became an impracticable course at night. It is now lighted by 10 incandescent lights of 100 candle power each, placed on the top of spar



RELICS OF A CUBAN INSURRECTION.

ordinary, and almost inclusively in future. The method of its application 50 foot cedar buoys which are shackled to 5,000 pound credible, for a model engine such as is described; yet will at once suggest itself to every manager. For much some such as is described; For mushroom anchors. The cable is constructed of a cop- it indicates a waste, by conduction and radiation, per conductor, insulated with gutta-percha, then bedded with jute and sheathed with an armor of hard heat sent to the machine from its boiler. - Science, according to the Engineering Record, a pressure of If much is used at any special points a barrelful can tance of 6½ miles. The generating station is located as the brine will not evaporate in cold weather.

Seven 12 inch nickel steel tube army rifles have recently been completed at the Watervliet arsenal with about 2,000 feet back from the beach. The current for a variation in weight between the lightest and the through a lead-covered conductor laid in a creosoted subway 4 feet underground. The electric plant is in duplicate. The current is generated at 100 volts and is raised by a step-up transformer. All the high-tendesirable, the flow being regulated by a cock. For sion lines are either underground or in cables at the bottom of the sea.

ALUMINUM felloes in bicycles are regarded by some

A New Quadruple Expansion Engine.

Messrs. Hall and Treat announce, in the Sibley Journal of Engineering for April, "A New Quadruple Expansion Engine." This machine, built for regular working at 500 pounds pressure, and with its boiler tested to 1800 pounds, has now been in operation in Sibley College, at Cornell University, for many months. It was designed by the authors of the paper, built by them in the shops of the college, and has since been tested under a great variety of conditions. The design was entirely original, although, of course, embodying the principles taught them in their college course, the one being a graduate of '98 and the other of '94, and both now candidates for advanced degrees, the one for a doctor's, the other for the master's, degree in engineering. The valve gear is new and the

by application of their text book and lecture room work: and the engine as a whole is a success. The boiler has worked well and economically up to above 600 pounds per square inch. and its waste heat is utilized in the reheating apparatus of the engine and so thoroughly as to make the temperature of the chimney very low. The steel for "running parts" was obtained from the Bethlehem Iron Company and proves to be of very ane quality. Special devices have been required, in every direction, to make the operation of the machine with such high pressure steam satisfactory and safe. Even the injector was necessarily reconstructed, as no ordinary instrument would force water into the boiler against 600 pounds pressure. The figures reported for economy are something under 10 pounds of steam per horse power per hour, and the best conditions of operation are not yet fully identified, though unquestionably corresponding closely with the preliminary computations of the designers. This figure is the lowest yet reported, even for engines of many times the size of that here described. It will require authoritative revision and corroboration; but there seems no reason to doubt its substantial accuracy, as the result of many engine trials under a great variety of conditions. If thus corroborated, it will stand as the "record of the world" for the nineteenth century. The thermodynamic consumption of this engine should be about 7 pounds of steam per horse power per hour, exclusive of all thermal wastes, and this should be approximated much more closely in engines of similar type built on a large scale. The figure attained is extra-

after all, of no less than twenty-five per cent of all

Manufacture of Great Guns.

lighting the buoys is carried to the submarine cable | heaviest of only five pounds. The guns are forty feet long and weigh approximately 115,000 pounds apiece. Each has an inner tube over which a series of hoops are shrunk for nearly the entire length. Over these is a single jacket two-thirds the length of the gun, and over this again are shrunk more hoops. Aside from this large number of parts, the guns are turned on enormous lathes during certain stages of their manufacture, and the close agreement of the entire lot is considered a remarkable feat of accurate workmanship.

THE CASSEUIL DRAWBRIDGE.

Drawbridges were in common use in the middle ages, and even the smallest castle was provided with one The use of them was seemingly falling into desuctude, but for some little time past the exigences of modern communications have been leading engineers to bring them to the front again. In order to render the maneuver easy, an endeavor has been made to balance the flooring in all its positions. In the bridges of the middle ages that we have just alluded to, this condition was rarely fulfilled, and, more correctly speaking, way to build a chimney, and as the products of com-

so absonever was

Poncelet, the celebrated bridge builder, occupied himself with this question. In 1810, Derche, another investigator, devised a counterpoise winding around a grooved wheel in spiral form. We may mention, further, a system due to Belidor. All these bridges were of wood. Since iron has entered into the construction of bridges, the system has become developed. In 1856, a drawbridge with a compensating balance frame was establish-

drawbridge. More recently, analogous drawbridges have been constructed over the Charleroi Canal, at Brussels.

Fig. 1.-THE CASSEUIL DRAWBRIDGE CLOSED.

The drawbridge that we are about to describe is constructed over the lower arm of the Drop, a tributary of the Garonne, near Caudrot (Gironde). The Drop, through its division into two arms, forms a very fertile island, whose various portions belong to persons who do not inhabit it on account of its low position, which renders it very easily inundated. The upper arm of the river, which alone is navigable in ordinary times, flows into the Garonne through a lock that no longer operates when the water reaches a height of 15 feet above low water mark. The boats then take the lower arm, where they consequently navigate only very accident-

high and would have required inclined approaches, whose cost would have taxed the fund disposable out of all

proportion.

Mr. Clavel, government engineer, who has been at the head of the vicinal service of the Gironde for some years, and who, during his administration, has endowed the department with several remarkable works, thought that the economical and practical solution of the problem resided in the use of a drawbridge.

A project was drawn up in this direction which met with approval on every side. The work is now constructed and is operating to the entire satisfaction of all interested.

After this expose, and with a reproduction of two photographs that show the bridge open and closed (Figs. 1 and 2), a technical description does not appear to us to be necessary. Let us merely add that the bridge has three spans, and that it is the one of the right bank that is movable.

The boatmen themselves do the maneuvering when wish to give passage to their vessel. Such maneuvering, however, is exceedingly easy, it being possible for one man to lift the flooring by acting upon a chain attached to the free extremity of the balance frame.

In this way the expenses of surveillance have been saved. Let us repeat that in many


cal application.—La Nature.

The Draught of Chimneys.

Some chimneys are made smaller at the top than at the base of the flue; others are larger at the top; and still others are of uniform size throughout, according to the fancy of those who designed them, writes W. H. Wakeman in Power and Transmission. Those who pipe and other apparatus, the most successful being advocate the first, claim that it is the most natural

> bustion ascend they become cooler, consequently contract, and do not need as much space as when they commenced their ascent. Advocates of the second, while they admit that the gases contract on cooling, call attention to the fact that as the chimney is higher, the fricincreases rapidly. and so deem it advisable to enlarge area of the chimney or stack, as the draught is materially increased thereby. Those who are in favor of the third tell us that the contrac

ed upon the Haute Marne Canal in order to allow pas- tion of the gases and other products of combustion sage to a railway. This work is known as the Marneval counterbalances the friction, and so a flue of uniform size is correct. Each can show chimneys built according to their ideas which are doing good work, but it is a hard matter to show that the same draught could not be obtained with a chimney built according to another design, and until this is done the matter of which is the best must remain an open question.



The nickel steel armor plates, as furnished the later vessels of the United States navy, are by the Harvey process hardened on the face to a depth varying from one-half inch to three-fourths inch. This face is such that it successfully resists the hardest steel drill that can be made, and as it is required in the final location annealer, and the engine for driving the same. The ally and at high water. Under such circumstances the of the plate to drill and tap numerous holes in it, it engine develops at 450 revolutions per minute 55 horse

similar bridges will find a practical and economi- the desired places by preventing the carbonizing material from coming in contact with them. The operation was not entirely successful, however, as it was found upon trial that although a number of the places were sufficiently soft to be worked, others immediately alongside were as hard as the unprotected portions. A number of attempts were made to locally anneal these hard spots by means of the oxyhydrogen blow-





Fig. 2.-THE DRAWBRIDGE OPEN.

that offered by the Thomson Welding Company, of Lynn, Mass. It was found impossible by all other means than electricity to apply sufficient heat in a concentrated form to attain the desired results, as the large mass of metal surrounding conveyed the heat away as fast as it was supplied. One of the electric welding company's annealing equipments has recently been installed at the Union Iron Works, San Francisco, for annealing the armor plates of the battle ship Oregon, and the following is a description of the plant and its operation:

The apparatus in general consists of an alternator, with its excitor, a regulating rheestat, a transformer bridge to be constructed would have had to be very was necessary during the hardening process to protect power. The alternator and exciter are of the well

> known commercial type; the former, of 40 k. w. capacity, has six coils on as many pole pieces, the windings being in two series of three in multiple. The armature is of the toothed type, with six coils, connected in a multiple of three series of two. It is wound for an output of 135 amperes at 300 volts, when making 1,000 revolutions per minute. A pulley on the end of the armature shaft drives the exciter. a D type shunt wound generator of 100 volts, at 2,000 revolutions per minute. Its terminals are connected to alternator fields through the regulating rheostat, a cylindrical frame, having German silver coils cut into or out of circuit by a contact arm on top. The coils are protected from mechanical injury by the wire gauze covering, which arrangement permits of a constant circulation of

The transformer annealer is of the shell type, and consists of an outer core of laminated iron surrounding both primary and secondary coils, the former being wound on a form, and incased inside the latter, which is a hollow copper casting made in haives to receive it, and then bolted together, after which the remaining space is filled with oil for insulation and as an assistance in conducting away the heat generated in the primary. The secondary coil has but a single turn, U-shaped, to the ends of which are bolted various shaped copper



THE ANNEALING OF ARMOR PLATES BY ELECTRICITY.

water circulation, thus preventing the heat of annealing from reaching the coils. The yoke from which the transformer is suspended by two trunnions, as well as the afore-mentioned contact pieces, permit of the transformer being swung into any desired angle, and brought against any part of plates already located.

In the operation of annealing, the contact pieces are brought up against the brightened surface of the plate and wedged into position, straddling the spot to be annealed, after the regular rheostat has been adjusted to a point reducing the primary current to a minimum. The distance between the contact pieces for a hole % of an inch in diameter is 1% inches. When the contact is established between contact pieces and the plate, a slight humming noise notifies the operator, and the primary current is gradually raised to its maximum. A bright red spot then appears under each contact piece. The intense local heat at these spots causes the plate to expand outwardly in the direction of least resistance, forming slight mounds, from which circles of a gradually changing color slowly approach the center. The primary is kept up till the plate has become sufficiently heated to char or even ignite a pine stick held against it, and is then gradually decreased, till it has again reached the minimum.

The first or heating period requires about three minutes, duing which the secondary current has reached from 3,500 to 6,000 amperes at four volts. The second or ecoling period requires from ten to twelve minutes, in order to permit the sudden chilling of the spot due to the surrounding mass of metal, and to insure a perfect anneal. The plate at the spot of annealing presents a dark blue color, elliptical in shape, with a major axis of 4 inches and a minor axis of 21/4 inches, and is very readily drilled and tapped.

The cut shows the annealer at work on a 17 inch plate for the Oregon's 13 inch barbette. A portable drill press driven by a direct current motor is shown in the background, ready to drill the holes as fast as the plate is annealed. The regulating rheostat is shown in the lower right hand corner. Four wires are led from alternator and exciter to a convenient spot, and connected to annealer and regulating rheostat has been able to ascertain that there was a remarkable through a flexible four-wire cable.

to Mr. W. S. Garton, of the Thomson Welding Company, for information in regard to the apparatus, and also to Mr. Ratto, photographer of the Union Iron Works, for the photograph herewith presented .-Pacific Electrician.

Natural History Notes,

Singular Case of Commensalism.-A singular case of commensalism, says the Revue Encyclopedique, has It just been made known by Mr. Gadeau de Kerville. concerns the young of the marine fishes called false mackerel, which are almost always found in company with the large medusæ known as rhizostomes. These young fishes swim parallel with the long axis of the jelly fish and in the same direction as the latter. They remain above, beneath, and behind the animal, but never advance beyond its umbel. It frequently happens that some of them introduce themselves into the cavities of the jelly fish, and are then visible from the exterior, owing to the transparency of the host. Sometimes the school of fishes wanders a few yards away from the medusa, but, at the least alarm, immediately returns with great rapidity to occupy its former position. It is evident that the medusa very efficaciously protects the young fishes by means of its innumerable stinging capsules. This is demonstrated by the fact that when the fishes become larger they no longer protect themselves by accompanying the medusa

Preserving Sea Weeds.—The following recipe is recommended by Dr. J. P. Lotsy for preserving examples of Floridez for microscopic examination: "The specimen is first laid in a 1 per cent solution of chrome alum in sea water and kept there for a period varying from one to twenty-four hours, according to the size and texture of the species. The chrome alum is then completely washed out and the specimen placed in a mixture of 5 ccm. of 96 per cent alcohol in 100 ccm, of water and vigorously stirred. The amount of alcohol is then increased by increments of 5 ccm. every quarter of an hour until it amounts to 50 ccm. The specimen is then removed and placed in a mixture of 25 per cent alcohol in distilled water, and the quantity of alcohol eem. alcohol to 100 eem. of water. The same process lutions of alcohol in distilled water; the specimen being finally preserved in the last,

of one in which thirst is the longest endured. But Mr. S. M. Gorman, of Cambridge, Mass., writes to Nature that more striking cases of prolonged endurance are found in a number of small rodents that inhabit the arid plains in the vicinity of the Rocky Mountains. These animals live for weeks and months without meeting with a single drop of water. The sand is torrid, the entire vegetation is burned up, and yet they resist. out giving any definition of what a species is. It is im- and 121 seconds.

contact pieces, which are hollowed and connected to a This is not the result of observation solely, for direct experiment has been made. Some common mice were put apart on the first of last October in cages in which they received nothing but perfectly dry food, such as Indian corn and grass seeds. On the seventeenth of January they were in perfect health and seemed as if they would continue thus for a long time, although they had not received a single drop of water or of any other liquid in the interim.

Activity of Animals.-In a recent number of Science Mr. Stewart gives the results of some interesting experiments upon the activity of animals that were made upon rats, mice, and squirrels inclosed in circular cages so arranged that every motion of the occupant caused the cage to revolve. An automatic apparatus permitted of registering the motions of the cage and of consequently ascertaining the periods of rest and activity of the animals. Rats and mice divide their time into twelve hours of rest and twelve of intermittent work during the night. During the period of work, the intervals of activity rarely exceed one hour, and are separated by intervals of rest of a nearly equal duration. In winter the squirrel works almost continuously from twenty minutes to two hours in the morning, and sometimes a little in the evening also, but during the balance of the time it remains at rest.

The food has a marked influence upon the daily activity. As a general thing, the richer this is in protein, the greater is the activity. Fatty substances have a contrary effect. They reduce the activity of mice from six to eight hours to a few minutes of work a day. In order to ascertain the influence of alcohol there was given to four rats fed upon dry grain some of this liquid at proofs varying from 5 to 60 per cent, instead of water. This treatment, kept up for fifty days, showed no uniform effect of the alcohol.

All the animals experimented with did more work when the barometric pressure was high.

Animals in Sterilized Air .- By keeping animals in a specially devised apparatus designed to supply them with air in an absolutely sterilized condition and also feeding them with food as far as possible free from bacteria, Dr. J. Kijanozin, of the University of Kieff, decrease in their assimilation of nitrogenous matter. In conclusion, the writer wishes to tender his thanks | The reason suggested is that micro-organisms, when present, aid in the decomposition and peptonizing of the nitrogenous matter in the intestine, and it is thought that were the removal of all the micro-organisms from the intestine possible, the decrease in the assimilation of nitrogen would be still greater. The animals also lost weight more quickly than under normal conditions, and excreted more nitrogen and carbon dioxide. In a number of cases the animals died a few minutes, hours or days after the beginning of the experiment, and as yet it has not been possible to assign any cause for this result.

The Poison of the Ornithorhynchus.-The hind feet of the ornithorhynchus, "the mole with webbed feet and the bill of a duck" that puzzed zoologists so much for a long time, are provided with a solid spur connected with a gland. Have we here a poison gland? From some apparently trustworthy accounts that have is at least venomous at a certain season. A dog was wounded by one of these spurs three times, and the symptoms the first time were those of pain and somnolence, but there were no convulsions, titubations or trembling. Upon the two other occasions, the symptoms were less pronounced, and even null, thus indicating habituation. The poison has proved mortal to the dog in four cases, but in man the symptoms disappear without causing death.

Evolution among Plants.-At a recent meeting of the Massachusetts Horticultural Society, Prof. L. H. Bailey read a paper upon "Experimental Evolution among Plants." The speaker prefaced his remarks by saying that all thoughtful persons are now evolutionists, whether they know it or not. They believe in some kind of a transformation of species in the same way that they believe in the gradual unfolding and growth of human institutions.

Prof. Bailey then proceeded to consider the question: Do new species originate now? The notion that a species, to be such, must have originated in Nature's garden and not in man's has been left over to us from the last generation—it is the inheritance of an acquired character. Ray appears to have been the first to use again increased in the same way, till it amounts to 50 the word species in its technical natural history sense, and the matter of origin was an important factor in his is again repeated with 50, 60, 70, 80, and 90 per cent so- conception of what a species is. Linneus said: "We the beginning." Darwin elaborated the new concept Resistance of Vertebrates to Thirst.—The camel is tion that a species is simply a congregation of individthe animal that is oftenest mentioned as an example uals that are more like each other than they are like any other congregation, and declared that one new interesting subject for study than any more species added to the infinitude of already recorded ones. The old naturalists threw the origin of species back beyond known causes, while Darwin endeavored to discover

portant, when we demand that a new species be cre ated as a proof of evolution, that we are ourselves open to conviction that the thing can be done. The fact is that the practice of systematic or descriptive botany is at variance with the teachings of evolution. Every naturalist now knows that Nature does not set out to make species. She makes a multitude of forms which we, merely for purposes of existing methods of botanical description and nomenclature, call specie

The speaker then proceeded to show that there has been as wide a variation in very many garden plants as there is between accepted botanical species of the same genus.

Species making forever enforces the idea of the distinctness and immutability of organic forms, but study of organisms themselves forever enforces an opposite conception. The intermediate and variable forms are perplexities to one who attempts to describe species as so many entities which have distinct and personal attributes. So the garden has always been the bugbear of the botanist. Even the lamented Asa Gray declared that the modern garden roses are "too much mixed by crossing and changed by variation to be subjects of botanical study." He meant to say that the roses are too much modified to allow of species making. despair of systematic botanists is the proof of evolution.

If species are not original entities in nature, then it is useless to quarrel over the origination of them by experiment. All we want to know, as a proof of evolution, is whether plants and animals can become profoundly modified under different conditions, and if these modifications tend to persist. Everyone interested knows, as a matter of common observation and practice, that this is true of plants. He knows that varieties with the most marked features are passing before him like a moving panorama. He knows that nearly every plant which has been long cultivated has become so profoundly and irrevocably modified that people are disputing as to what wild species it came from. Consider that we cannot certainly identify the original species of the apple, peach, plum, cherry, orange, lemon, wine grape, sweet potato, Indian corn, melon, bean, pumpkin, wheat, chrysanthemum, and nearly or quite a hundred other common cultivated plants. It is immaterial whether they are called species or varieties. They are new forms. Here is the experiment to prove that evolution is true, worked out upon a scale and with a definiteness of detail which the boldest experimenter could not hope to attain were he to live a thousand years. The horticulturist is the only man in the world whose distinct business and profession is evolution. He of all other men has the experimental proof that species come and go.

Formation of Secretions in Plants.-Dr. A. Tschirch announces, in the Botanisches Centralblatt, the remarkable discovery that in all normal cases which he has been able to examine the formation of a secretion it is a function, not of the protoplasm, but of the cell wall. In schizogenous passages the secreting cells which clothe the canal contain a resinogenous layer, which is often vacuolar; in schizo-lysigenous cavities the secretion is formed in peculiar caps of cell wall belonging to the cells which inclose the space. In the reached him, Mr. Stewart thinks we have. This gland oil glands of the Labiatæ, Compositæ, etc., it is produced entirely in a subcuticular layer of the cell wall, and this is the case also with the papille which project into the intercellular spaces of the rhizome and base of the leaves in Aspidium filix-mas, and in many, if not all, extra-floral nectaries, the secretion lifting the cuticle off from the palisade-like secreting tissue. In all stigmas examined by the author, the secretion is formed in the subcuticular mucilaginous layer of the papille, into which the pollen tube makes its way. Similar observations were made on the oil of oil glands and on the resin which is formed in the duramen of trunks. But, although the secretions are formed in the cell wall, they are never produced by metamorphosis of the substance of the cellulose itself. Dr. Tschirch ascribes to all resins a uniformity in chemical composition, regarding them as compounds of aromatic acids with a peculiar group of alcohols which he calls

Tests of the Maxim Gun.

The light weight, rapid fire Maxim gun, though not new, has been greatly improved of late and in its present form was given a comprehensive series of tests at Sandy Hook on June 8. The gun weighs, packed in its case together with all its extra parts and mechanism, only 45 pounds, and is easily carried on a soldier's back. When in use it stands upon a tripod. The reckon as many species as there were forms created in cartridge contains 28 grains of smokeless powder and a ball of 0.302 caliber, and a rate of from 600 to 770 shots a minute is claimed at 3,200 yards effective range. A range of only 500 yards was selected for the test. The gun was taken from a man's back, assemvariety raised by man will be a more important and bled and fired in 58 seconds. About 500 shots a minute were fired and no attempt was made to greatly exceed this rate. In the breakdown test an essential part of the mechanism, supposed to have been broken by a shot, was taken out and replaced by a new one their origin; and it is significant that he set out with- in 26; seconds. The barrel was changed in 1 minute

THE FOUNTAIN AT GENEVA.

Our engraving represents the fountain that the municipality of Geneva has recently established at the entrance of the port of that city, at the extremity of the south jetty. This is certainly the largest fountain that exists upon the surface of the globe, since it is no less than three hundred feet in height. It may be seen from a great distance, in clear weather, detaching itself like a great white sail flapping through the effect of the wind.

The city of Geneva possesses a most complete distribution of water under pressure, the motive power for which is obtained from an artificial fall established upon the Rhone at the point of the lake. The water for domestic purposes and for the running of certain motors is raised to a height of 215 feet above the level of the lake. For the distribution of motive force, it is raised to a height of 400 feet. The reservoir is an open air one, and is situated upon the top of Bessinges, at a distance of three miles from the turbine building. A very ingenious regulator, invented by Mr. Turrettini, assures the uniformity of pressure in the piping.

The length of the first pipe line is about 40 miles, and that of the second about 60. It is with this latter that the fountain conduit is connected. The latter is set in play only on Sundays. It is sometimes set in operation also on week days, in the evening. Instead of a single jet of great height, several are then utilized that do not rise so high. Powerful electric light projectors, placed in a structure near by, brightly illuminate them with their rays of varied colors, which in the middle portion encounters a rocky ridge, necestransform them into a luminous fountain of the sitating a cut about 260 feet deep in one part. The the canal was formally opened for general traffic on most beautiful aspect.-La

Safer Than Lightning Rods,

Nature.

Each day adds some new virtues to the long list of those already credited to the pneumatic. The latest of these is that the wheels of a bicycle being encircled by a band of India rubber and dry air-which is a perfect insulator - the rider is completely insulated from the earth, and, consequently, is impervious to the attacks of the electric fluid. Thus, day by day it becomes more and more a fact that life without a pneumatic tire is neither safe nor worth having. Any one who suffers from nervousness during a thunder shower has now only to go into a barn or the cellar and seat himself upon the saddle of a pneumatic-tired bicycle to be perfectly safe from lightning stroke. As the chances of a man on a bicycle being struck by lightning have been carefully calculated to be about one in a billion, the Wheel

matic as a lightning insulator amounts to very much.

Ancient Glass,

The glass blowers of ancient Thebes are known to have been as proficient in that particular art as the most scientific craftsman of the same trade of the present day, after a lapse of forty centuries of so-called "progress." They were well acquainted with the art of staining glass, and are known to have produced that commodity in great profusion and perfection.


Rossellini gives an illustration of a piece of stained glass known to be 4,000 years old, which displayed artistic taste of high order, both in tint and design. In this case the color is struck through the vitrified structure, and he mentions designs struck entirely in pieces from 1/4 inch to 3/4 inch thick, the color being perfectly incorporated with the structure of the piece, and exactly the same on both the obverse and reverse sides

The priests of Ptah at Memphis were adepts in the glassmaker's art, and not only did they have factories for manufacturing the common crystal variety, but they had learned the vitrifying of the different colors and the imitating of precious stones to perfection. ture that even now, after they have lain in the des- draught vessels direct access to the important manufacert sands from 2,000 to 4,000 years, it takes an expert to distinguish the genuine articles from the spurious. It has been shown that, besides being experts in glass by Liverpool, and the canal project encountered active making and glass coloring, they used the diamond in opposition from interests identified with this port and cutting and engraving glass. In the British Museum there is a beautiful piece of stained glass, with an engraved emblazonment of the monarch Thothmes III. who lived 8,400 years ago.

The New European Ship Canals,

The opening of the Corinth Canal in Greece and of the Manchester Canal in England having now been followed by the practical completion of the Baltic and North Sea Canal in Germany, a review of some of the salient features of these important works is opportune. While they possess many points of similarity, they present marked differences in the purposes they are intended to serv

The Corinth Ship Canal affords a passage from sea to sea and is intended to meet the needs of commerce by shortening a route which is not, however, one of the highest degree of importance. Taking advantage of the fact that the Gulf of Corinth, lying in a general easterly and westerly direction, nearly separates Greece into two parts, this canal pierces the narrow Isthmus of Corinth and thus furnishes a passage from the Gulf of Corinth on the west to the Gulf of Ægina on the east. It thereby shortens the sea route from the western Mediterranean and from the Adriatic to the seaports of Eastern Greece, Turkey, Asia Minor and the Black Sea. The distance saved differs considerably in different cases, depending upon the ports of departure and destination, but is not more than 185 miles in any This canal is about 4 miles in length and has a minimum width of 72 feet at the bottom and 77 feet at bottom is 120 feet. The sides are protected by masonry, the surface of the water, the sides rising very abruptly where this seemed advisable, the aim being to permit the surface of the water, the sides rising very abruptly and being faced with masonry to a height of several feet above the water level. The minimum depth is 26 feet. The axis practically follows a straight line which hours. By the use of electric lights the canal is made passes through a low country toward either end, but navigable by night as well as by day. The prelimi-



THE GENEVA FOUNTAIN.

adds, there will, of course, be some pessimists who will | total quantity of earth and rock removed is estimated | promptly between them and concentrate in either sea deny that this newly discovered virtue of the pneu- at 11,500,000 c. m. Breakwaters and artificial harbor works have been found necessary at both entrances. A high bridge, carrying the Piræus & Peloponnesus Railway, crosses near the western end. The canal is lighted at night by electricity.

> The formal opening of the Corinth Canal, which took place in August, 1898, marked the final achievement of a scheme dating back in one form or another to ancient times. The work as completed follows closely, in some parts at least, the line of a similar undertaking on which much labor was expended in the time of Nero. The modern project dates back to 1881. Work began in 1882 and was prosecuted vigorously for some years, but in 1889 ceased for a time owing to lack of funds. The enterprise was afterward taken up by a new company, the Société Hellenique du Canal de Corinthe. Work was resumed in 1890 and carried to a successful conclusion in 1893. The total cost was about \$18,000,000. The lease held by the present company is to continue in force for 99 years, at the end of which period the canal is to become the property of the Greek government on the payment of \$1,000,000.

Turning now to a much larger and much more costly turing city of Manchester. Formerly it was necessary to depend chiefly upon the shipping facilities afforded from the railroads affected. Authority having been cussion extending over a period of several years, and a company having been formed, the work of excavation of silver and 81/2 parts copper,

began late in the autumn of 1887 and was pushed forward with energy. Unexpected delays occurred later, owing to financial embarrassment and other cause but all difficulties were overcome and the enterprise was carried through to completion within the space of six years. It was believed at first that four years would be sufficient and that the cost would not exceed \$30,000,000. The actual outlay was about \$75,000,000. Although Manchester is 50 miles from the sea, it was not necessary to carry the canal this entire distance, as the tidal estuary of the Mersey furnished an approach for about 15 miles from the sea. Throughout the remaining 35 miles existing water courses were enlarged and utilized wherever practicable, including along one part of the route an old canal of small cross section. As Manchester has an elevation of 60 feet above the sea level, an ascent of this amount was necessary, and was accomplished by a system of locks. The line of the ship canal is crossed by a number of highways and railroads, besides a smaller canal, and numerous engineering problems were encountered. In some cases fixed bridges were required; where these occur they have a minimum height above the canal of 75 feet in the clear. The minimum depth of the canal is not less than 26 feet, and the minimum width at the a speed of about 6 knots, thus enabling a vessel to pass from the entrance up to Manchester in eight or nine

> January 1, 1894. It may be added that Manchester is the center of a district said to be more thickly populated and to show a greater output of commercial products than any other region of like area in the civilized world. The density of population is 18 times as great as that of Belgium, which is said to have more inhabitants to the square mile than any other country of Europe. The Manchester region contributes two-thirds of the total value of British exports.

The Baltic and North Sea Canal differs from the other two, concerning which some details have just been given. in that it owes its construction primarily to political and strategic considerations rather than to the commercial advantages which will incidentally result from it. Germany has two naval yards of great importance, one at Kiel on the Baltic and the other at Wilhelmshafen on the North Sea, and in order that vessels may be able to pass

the ship canal has been cut under the auspices of the German government. It extends from Kiel to the River Elbe, entering the latter at a point below which deep water extends to the North Sea. Commercially the canal is important in the saving of time heretofore lost in going around the northern end of Denmark and in making it possible to avoid a stormy and dangerous passage. The distance saved between ports is from 100 to 425 miles, according to their relative position. The canal is practically a sea level one, there being tidal locks at the ends, but none along the course of the waterway. It was necessary to build several bridges over the canal, but they do not interfere with navigation. The fixed bridges, of which there are two, have a height in the clear of 138 feet. The cutting was largely through a low country, following an old canal in part. At the highest point there is a ridge rising 82 feet above the sea. There are several sharp turns, though the general course is a fairly direct one. The canal is 61 miles long. The standard depth is to be 29.5 feet upon final completion in all parts. The width at the bottom is 72 feet. Work on this canal began in 1887. It was then expected that it would be necessary to excavate about 77,000,000 c. m. of material, but this the imitating of precious stones to per-work, the Manchester Ship Canal, special mention estimate was too small by from 3,000,000 to 5,000,000 c. Their imitations of the amethyst and of should be made of the fact that the main purpose m. The total cost of the canal amounts to about \$40. the various other colored gems were so true to na- served by this great artificial waterway is to give deep 000,000, of which Prussia pays about one-third, the remaining part being paid by the German Empire.-Iron

> TWENTY-FOUR carat gold is all gold; 22 carat gold has 22 parts of gold, 1 of silver and 1 of copper; 18 carat gold has 18 parts of pure gold and 8 parts each finally granted by Parliament, after a prolonged dis- of silver and copper in its composition; 12 carat gold is half gold, the remainder being made up of 81/4 parts

RECENTLY PATENTED INVENTIONS. Railway Appliances,

CAR COUPLING. - Valentine Erbach Scranton, Pa. This improvement of Scranion, Pa. This improvement comprises a drawbead having at the sides noses, one below the other, with oppositely inclined upper and lower faces and parallel sides, and having vertical perforations, while a gravity link is arranged in the perforation in the upper nose. When the drawbeads come together they are positively guided to coupling position and the coupling is automatically effected, and means are also provided whereby any desired number of steam and compressed air piges may be simultaneously and automatically compact. be simultaneously and automatically coupled.

CAR FENDER .- James L. Canham. This is a device to be readily at tached to or detached from the dashbourd of a car, and of such construction as to present a yielding bed to any one falling on the fender. The parts are so arranged that the sagging caused by a body falling on the fender operates a trip and causes an auxiliary bed to be projected, as a further protection for a person caught in the path of the car.

Electrical,

GENERATOR.-John D. Hilliard, Jr., Bluefield, West Va. This is a compound wound alter nating generator, with improved means of com and regulating the voltage, there being two wis the field spools of the generator, one of which is fur-nished with a constant current from a separate exciter, and the other with a variable current supplied by the ator itself and varied with the variation of the load to generator. The regulation of the voltage is quick and efficient, as there is but one magnetic field to

GALVANIC BATTERY CELL-Frank A. Glasgow, St. Louis, Mo. This is a small, easily porta-ble cell, in which a tube or easing closed at the upper end is placed over the sinc or positive element, displacing the fluid from about the element, and protecting it from being destroyed when the cell is not in use, while the air or gas in the tube displaces the fluid when the tube is pushed down over the zinc. In the protrusion upward of the zinc from the bottom of the cell the exposed portion of the positive element stands free from support.

INSULATOR-James M. Patterson, Springtown, Texas. For insulating and supporting tele, graph and telephone wires, this inventor has devised an fineliator comprising two sections of insulating material adapted to fit together and each having on its inner sides a longitudinal recess, in which blocks notched on their inner faces are to be inserted, the insulator being of a very simple and inexpensive character, and adapted to clamp the wire securely and prevent its longitudinal

ALARM SIGNAL AND INDICATOR-Jacques A. Buisson, New Orleans, La. This is a derice for trolley reads, to be applied especially at crossings, carves, tunnels, and other dangerous places. Combined carves, tunnels, and other dangerous places. Combined with the main trolley wire is a short suxiliary wire connected with the alarm and signal, and a double trolle; establishes electrical connection between the main and qualitary wires to cound an alarm and give a visible sig-nal as the car passes along the portion of the track to be

Mechanical.

PAPER MAKING MACHINE.-Thomas H. Savery, Wilmington, Del. This invention relates to the wire part of high speed Foudrinier machines, in which the water from the pulp residing upon and carried by the wires over a series of table rolls is directed and caused to flow into save-all boxes, and provides table rolls adapted. to support the wire, with deflectors interposed between the rolls and extending downward to the plane or level of the lower surfaces of the rolls, to provent the water being thrown from one roll to the adjacent roll.

Miscellaneous.

STENOGRAPHIC MACHINE.-Joseph W. and Joseph K. Bailey, New Orleans, La. This is a ma-chine in which the characters are formed by puncturing devices which penetrate and form a permanent record on a strip of paper, the machine being also adapted for printing as well as puncturing. The machine has a closely grouped set of horizontal and parallel bars with converging ends provided with properly shaped dies, hor izontal rock shafts arranged at right angles connecting with the die bare and a series of vertical keys, there being means for connecting the keys to the rock shafts the rock shafts to the die bars.

TIRE TIGHTENER. - Jasper N. Jenninzs, Portland, Oregon. According to this improve-ment, in a foot section adapted to fit on the wheel bub is journaled a screw carrying a interally extending liftin arm, a not threaded on the screw having a interally of terding arm on which a hook is adjustably held. The device is strong, cheap, and simple, and may be readily applied to any wheel to quickly tighten the tire without removing the wheel from the axie, It also facilitates spreading the wheel for the removal of the spokes if no meany, the straightening of the tires, etc.

HORSE COLLAR FASTERER.-John H. St. Joseph, Mo. This inver two caps to fit over and inclose the collar ends, each cap | ble adjustment and good fit of the garment. being divided horizontally and provided with securing tongs having bolt holes. The cap sections have overlapping portions to prevent slipping and locking lugs and hooks to secure them together and fasten the collar. The kame strap passes between pairs of registering luss, and the device is easy to fasten and unfasten, holding the collar securely when in fastened position.

water with lime paste to purify it, then charging the mix-ture with carbon dioxide and subjecting it to the action of an electric current to separate and set free the carbon-ate of lime and the carbon dioxide. The electrolytical apparatos comprises a reservoir in which is an agitating device and provided with movable slatted frames form-ing one of the electrodes, a metallic perforated cylinder forming the other electrodes.

SEPARATING GOLD AND SILVER. Frederick Rinder, Chicago, Ill. For separating the gold and silver in a cyanide solution this invention provides a and sliver in a cyanide solution this invention provides a process consisting in first subjecting the cyanide solution to the action of a solution of sulphide of iron, to sepa-rate and precipitate the sliver, and then subjecting the cyanide solution, in a separate tank, to the action of chloride of zinc, to separate and precipitate the gold. The invention is an improvement on the "MacArthur-Format cyanide process." using but little chloride, and Forrest cyanide process," using but little chloride, and the process requiring but little attention and labor.

BALANCE.-Clarence N. Fenner, Pater n, N. J. In this balance the stand segment over its upper end, and the scale beam has verti-cal longitudinally aligned set screws, having between their inner ends the middle knife edge engaging the their inner ents the middle knife cage cazaging the upper end of the standard. The beam also has knife edges at its ends from which the pans are suspended, while a weighted inclined arm extends down from the center of gravity at the middle of the beam, there being a similar inclined pointer above the center of gravity and working over the segment. The improvement is de-signed for use on all classes of balances, including the most delicate and those for weighing merchandise.

ANTI-FRICTION BLOCK. - Gregory M. Mullen, Baltimore, Md. This block is especially designed for use in guiding the tiller ropes of tugs, yachts, etc., renoting the friction to permit the free and easy move-ment of the sheave. There are side rollers between the sheave and journal, terminating short of the end of the sheave, providing an annuar cavity surrounding the and a fiange or rib of the cap jaw entering the The sheave has its under side channeled and balls fit between the sheave and the main jaw.

BATH OR OTHER TUB. - Charles E. Marston, Dover, N. H. This invention provides mean for keeping the water in the tub at a uniform tempera ture as long as desired, and also for quickly raising or lowering in temperature. A shower or spraying device is also provided to spray from the sides, and the tab may be utilized to heat the air surrounding the bather and maintain the required temperature in the room, the tub acting as a radiator. The tub may also be used as a

CHURN POWER.-John T. Gilbert, Combus, Ga. A turning as well as a reciprocating a is given to the churn dasher in a very simple and effect tive manner by this improvement. In a vertical frame is hold a shaft at whose lower end is the dasher, and on whose upper end is revolubly held a head pivotally con-nected with a pitman, the latter being connected with the crank arm of the drive shaft. In the shaft is a spiral groove engined by the tip of a set scrow, whereby the shaft is rotated as it is reciprocated.

CLOTHES LINE FASTENER.—Charles L. Feinberg, Brooklyn, N. Y. This is a simple device for quickly and firmly uniting the two ends of a pulley line and to facilitate taking up the slack at any time. It sists of two parts pivoted together, the outer end of part terminating in an eye to which one end of the line is tied, while the two sections form at the other end a clamping jaw in which the line will be held by the pres-

WINDOW SHADE. - Joseph Eckert, New York City. A shade is constructed of a series of strips or sections, according to this improvement, each section being capable of movement to or from an adjoining section, providing for larger or smaller spaces for the admission of light, while the shade sections are adjustable to admit light and air without admitting the sun directly. The improvement comprises a series of independent rollers and locking devices, with a bur detachably con-nected to the lower parts of the shades, and all of the s may be simultaneously manipulated.

LIQUID COOLING CAN.-Wolff F. E. Casse, Copenhagen, Denmark. For preserving and storing milk, cream and other liquids or food this inventor has de-vised a vessel having a jacket adapted to contain ice and prevent the water formed in the ice jacket from coming in contact with the inner wall of the jacket until nearly all the ice is melted. There are ice-holding hooks or pro-jections in the inner wall of the vertical part of the jacket which prevent the ice from rising as the water is formed by thawing, and are thus designed to preserve the con-tinuity of the layer of ice on the inner wall of the jacket.

ILLUMINATED COLUMN.-Charles Sieeg, New York City. In fixtures for offices, bars, etc. this invention provides a column designed to heighten the ornamental effects. The invention comprises a base on which is a hollow shaft of translucent or transmaterial with a capital of opaque material in which is held a lighting device, preferably an electric light, adapted to throw its light down into the shaft to illumin latter from the inside. The arrangement is such that the shaft can be taken down and cleaned, and ready acc the lamp is provided for.

BICYCLE TROUSERS.—Henry J. Roschi, New York City. These are garments adapted to give efficient support to the abdomen and other parts of the body, and they have elastic gores at the waisthand and novel leg attachments adapted to relieve strains and obviate any danger of rapture, while insering a comforts the advice given by Nystrom: "Every engineer should

GAME APPARATUS.—Charles H. Buxton, Neenah, Wis. A game similar to that of base bull may, according to this invention, be played by a simple and inexpensive device with which runs may be scored, the player put out, the circuit of the bases made, etc., in manner elmulating that of a regular game. The field is

Besigns.

CANDLESTICK.-William Varney, New York City. This design comprises a representation of a flower and a cup somewhat concealed among the leaves, together with a foliage support in which are stems,

ROLLING HOOP. - Francis C. Bates, Newport, Vt. In this hoop is a central star-like figure consisting of a circular disk having a double series of radial projections, and between the central figure and the hoop are connecting cords.

Norz.—Copies of any of the above patents will be furnished by Munn & Co., for 25 cents each. Picase send name of the patentee, title of invention, and date

NEW BOOKS AND PUBLICATIONS.

STEAM AND THE MARINE STEAM ENGINE. By John Yeo. London and New York: Macnillan & Company. 1894. Pp. xiv, 196. Price \$2.50. No index.

Naval steam engineering is a profession which is acquiring year by year a greater importance. The possibility of economy and the importance of achieving it on ship board have brought about some of the most perfect types of boilers and steam plants which have been devised. This is another way of anying that the naval steam engineer stands justly at the head of his profession, having to destign the most perfect power apparatus and to use it properly. The coal consumption is nowhere more closely watched than on a steam ressel, and in the present days of record trips the chief engineer is as important an office; as the captain. Although neer is as important an office; as the captain. Although we regret the absence of an index, a very full table of contents, to a certain extent, takes its place

REPORT OF THE BOARD OF GENERAL MANAGERS OF THE EXHIBIT OF THE STATE OF NEW YORK AT THE WORLD'S COLUMBIAN EXPOSITION. Transmitted to the Legislature April 18, 1894. Albany: James R. Lyon, State Printer. 1894. Pp. 647.

We will not attempt to describe this large volume. It is enough to say that it is an exhaustive synopsis of what New York State proper showed at Chicago, with numer-ons illustrations of the exhibits. We notice, among ous illustrations of the exhibits. We notice, among others, very satisfactory plates of the work shown by the Teuchers' College, recently illustrated in our columns, but as every third or fourth page has a full plate, it will be found a perfect album of the exhibits and of many that will have a homelike and funfiliar aspect to the New Yorker. We doubt if any State can produce a much more creditable report upon its exhibits. The large size of the plates makes them tend to be satisfactory, and we think that teachers and other professional workers will find the volume one of great value. Namerous portraits are given of the members of the Commission, while general views of the fair proper are not lacking.

ELEMENTS OF MINERALOGY, CRYSTALLO-GRAPHY AND BLOWPIPE ANALYSIS, FROM A PRACTICAL STANDPOINT. By Alfred J. Moses and Charles Lathrop Parsons. New York: D. Van Nostrand Company. 1895. Pp. vii, 342. Price \$2.

The joint authorship of this volume gives it value, as it involves the views of two somewhat separated institutions. The book is rather more a work on crystallography and the identification of minerals than a blowpipe manual of the neual kind, the application of the blowpipe to mineral identification being closely followed in it. The work is qualitative in the sense that quantitative analysis is not given. The liberal illustrations and thoroughly practical treatment make it quite an attractive addition to the literature of the science.

The Diseases of Personality. By
Th. Ribot. Chicago: The Open
Court Publishing Company. 1895.
Pp. 163, 16mo. Paper 25 cents, cloth
75 cents.

An authorized translation of the work of M. Ribot professor of comparative and experimental psychology in the College of France. He is also the author of "The Prohology of Attention" and "Diseases of the Will." The present work treats of organic disorders, affective disorders, disorders of the intellect, dissolution of pernality, scological individuality, etc.

CATECHISME D'ELECTRICITE PRATIQUE. By Ernest Saint-Edme. Paris: Bernard Tignol. Pp. 128. 16mo, 73 illustrations.

Under the attractive catechism or question and answer form the author has attempted to treat the whole subject of electricity in 138 pages. The illustrations are poor and do not show the later forms of apparatus. The work is undated and has no index.

THE MECHANICAL ENGINEER'S POCKET BOOK. A reference book of rules, tables, data, and formulæ, for the use of engineers, mechanics, and students. By William Kent, A.M., M.E. New York: John Wiley & Sons. 1895. Pocketbook, full gift, flaps. Pp. 1087. Illustrations, tables, etc. Price \$5.

make his own pocketbook, as he proceeds in study and practice, to suit his particular business." The results of Mr. Kont's judicious gathering of engineering facts and figures are found in the present admirable collection of rules, tables, and out of the way information. The scope of the work is different from that of Trautwine and Has-well and it would be a valuable acquisition to all who DISINFECTING AND PURIFYING WAThis invention is for a process and apparates for domestic and industrial uses, the process consisting in first mixing the bound to the movement of a ball over the industrial uses, the process consisting in first mixing the bound which constitutes the field.

The diamond are holes represent the bases, there being also slots to represent "outs," and the possess these important works. Much attention has been paid to the abstraction of data of experiments from recent literature. The section relating to ice machines is jumpled to the process consisting in first mixing the bound which constitutes the field.

section devoted to faels is also noteworthy. The greatest merit of the book consists in its furnishing in-formation which would require long search in the files of technical journals and the proceedings of professional icties. Even such subjects as jet propulsion stelly treated. Access to the stores of infor-Access to the st ed easy by an excellent index.

PRACTICAL DIRECTIONS FOR ELECTRIC
GAS LIGHTING AND BELL FITTING
FOR AMATEURS. By Edward Trevert.
Lynn, Mass.: The Bubier Publishing Company. 1895. Pp. 64. 16mo,
18 illustrations. Paper 25 cents.
This inexpensive little work contains an excellent
series of diagrams of connections which will be appreciated by all electrical bell fitters.

HISTORY OF EDUCATION IN MARYLAND.
By Bernard C. Steiner, Ph.D. Contributions to American educational
history, No. 19. Washington: Published by the United States Bureau
of Education. 1895. Pp. 331. 8vo, illustrated.

The present work forms one of the interesting monographs on the history of education by States. The series is edited by Dr. Herbert B. Adams, professor of American and institutional history in the Johns Hopkins University. Maryland has not obtained wide renown until recent years for her higher institutions of learning, and yet the number and importance of them has been too great to justify such neglect as they have received. The present work gives a succinct account of education in colonial Maryland, primary and secondary education, the first university comes in for a fair share of attention. The value of the work would be enhanced by an ladex.

THE PHONOGRAPHIC DICTIONARY AND PHRASE BOOK. By Benn Pitman and Jerome B. Howard. Cincinnati: The Phonographic Institute Company. 1894. Pp. 48. 16mo, pain-phlet. Price 10 cents for the first part; no other parts will be sold separately. The completed work will cost \$2.50 in cloth.

Any of the above books may be purchased through this office. Send for new book catalogue just pub-liahed. Munn & Co., 261 Broadway, New York.

SCIENTIFIC AMERICAN BUILDING EDITION.

JUNE, 1895,-(No. 116.)

TABLE OF CONTENTS.

cottage at Bronxwood Park, Williamsbridge, N. Y., recently crected for Dr. Geo. P. Shirmer, at a cost of about \$6.500. Perspective elevation and floor plans. A piessing design. A. F. Leicht. Esq., architect, New York City.

Baq., architect, New York City.
2. An elegant plate in colors showing a cotting at Bronxwood Park, Williamsbridge, N. Y., recently erected at a cost of \$3,300. Perspective view and floor plans. Mr. A. F. Leicht, architect, New York.

floor plans. Mr. A. F. Leicht, architect, New York
City. A neat design.

8. A cottage at Flatbush, L. L., recently erected for W.
K. Clarkson, Esq., at a cost of \$5,000. Perspective
elevation and floor plans. Mr. Christopher Myers,
architect, New York City. A picturesque design.

4. A modern cottage at Bedford Park, New York City,
recently erected at a cost of \$5,000. Perspective
elevation and floor plans. A picturesque design.
Mr. Edgar K. Bourne, architect, New York City.

5. The Bedford Park Congregational Church. Two
perspective elevations and floor and basement
plans. Cost complete, \$7,000. Mr. Edgar K.
Bourne, architect, New York City.

6. A Colonial cottage recently erected at New Dorp.
S. I., at a cost of \$3,675, complete. Perspective
elevation and floor plans. Messrs. Child & De
Geil, architects, New York City. An attractive

Goll, architects, New York City. An attra

dasign.
7. A residence at Germantown, Pa. Two perspective elevations and floor plans. Cost complete, about \$10,500. Mesers. Child & De Goll, architects, New

York City. 8. The New Theater, San Luis de Potosi, Mexico. Architect, Don Jose Noriego 9. Design for a window decoration

10. The residence of E. P. Sandford, Esq., at Montclair,

N. J. Two perspective elevations and floor plans.
An elegant design. Architect and builder, Mr. E.
P. Sandford, Montelair, N. J.

11. A cottage in the English balf-timbered style recently

A cottage in the English half-timbered style recently erected for F. E. Kirby, Esq., at Glen Ridge, N. J. Perspective view and floor plans. E. Rollin Tilion, designer, New York City.
Hiscellaneons contents: The Hanging Gardens of Babylon.—Perspective drawings.—Concrete roofs.

—Points of support.—Architecia' estimates.—An improved hot water heater, illustrated.—A new invention for raising water, illustrated.—Improved paving.—The Bommer spring hinge, illustrated.—A mixing regulator for cas machines. Illustrated. vention for raising water, insurance,—Improved paving,—The Bommer spring hinge, illustrated,—A mixing regulator for gas machines, illustrated,—Adjustable sliding door track and hanger, illustrated,—Woodworker's improved vise, illustrated, African mahogany.—A new steam and hot water heater, illustrated.—Powers' improved automatic ney top, illnets machinery, illustrated.

The Scientific American Building Edition is issued The Scientific American Building Edition is issued monthly. \$2.50 a year. Single copies, 25 cents. Thirty-two large quarto pages, forming a large and aplendid MAGAZENE OF ARCHITECTURE. richly adorned with elegant piates and fine engravings, illustrating the most interesting examples of Modern Architectural Construction and allied subjects.

The Fullness, Richness, Cheapness, and Convenience of this work have won for it the Larger Cinculation of any Architectural Publication in the world. Sold by all newsdealers.

MUNN & CO., PUBLISHEERS,

MUNN & CO., PUBLISHER

Business and Personal.

The charge for Insertion under this head is One Dollar a line for each insertion; about eight words to a line. Adver-tuements must be received at publication office as early as Thursday morning to appear in the following week's issue.

For mining engines. J. S. Mundy, Newark, N. J. "C. 8." metal polish. Indianapolis. Samples free.

Presses & Dies. Ferracute Mach. Co., Bridgeton, N. J. Handle & Spoke Mehy. Ober Lathe Co., Chagrin Falls, O.

Emery Wheel Salesman Wanted. Morgan, care Sci. Am.

Handle turning machinery. Trevor Mfg. Co., Lockport, N. Y.

screw machines, milling machines, and drill presses. The Garvin Mach. Co., Laight and Canal Sts., New York. Emerson. Smith & Co., Ltd., Beaver Falls, Pa., will send Sawyer's Hand Book on Circulars and Band Saws

The best book for electricians and beginners in elec-ricity is "lkxperimental Science," by Geo. M. Hopkins. sty mail. 84; Munn & Co., publishers, 361 Broadway, N. Y.

For the original Bogardus Universal Eccentric Mill, Foot and Power Presses, Drills, Shears, etc., address J. S. & G. F. Simpson, % to 36 Rodney St., Brooklyn, N. Y.

The Toy Windmill, illustrated and described on p. 4. Patent for the United States for sale, or inventor will ense parties to manufacture on royalty. Address ed, Beaumont, Jr., 1907 Franklin St., Kansas City, Mo.

\$\vec{\pi}\' Bend for new and complete catalogue of Scientific and other Books for sale by Munn & Co., \$\vec{\pi}\' Broadway, New York. Free on application.



HINTS TO CORRESPONDENTS.

Names and Address must accompany all letters, or no attention will be paid thereto. This is for our information and not for publication.

References to former articles or answers should give date of paper and page or number of question. In quiries not answered in reasonable time should be repeated; correspondents will bear in mind that some answers require not a little reasonab, and, though we endeavor to reply to all either by letter or in this department, each must take his turn.

Buyers wishing to purchase any article not advertised in our columns will be furnished with addresses of houses manufacturing or carrying the same.

houses manufacturing or carrying the same.

Special Written Information on matters of personal rather than general interest cannot be personal rather than general interest cannot be expected without remuneration.

Scientific American Supplements referred to may be had at the office. Price 10 cents each.

Books referred to promptly supplied on receipt of receipt.

Minerals sent for examination should be distinctly

(6563) J. C. B. says: 1. Will you be kind enough to give formula to make liquid glue similar to the Le Page glue? A. We have not the Le Page formula. A liquid glue possessing great resisting power, recommended for wood and iron, is prepared, according to Hear, as follows: Clear gelatine, 100 parts; cabinet makers' glue, 100 parts; alcohol, 25 parts; along a parts; the whole mixed with 300 parts of 30 per cent acetic acid, and heated on a water bath for six hours. An ordinary liquid gine, also well adapted for wood and iron, is made by boiling together for several hours 100 parts gine, 300 parts water, and 16 parts nitric acid. 2. Also simple and effective way to remove warts on face? A. Castor oil constantly applied from 2 to 4 or 6 weeks, each day, that is, once a day; it has not failed in my hands, says a writer in the Therapeutic Gazette in any case of any size or long standing. The time i takes may try the patience of the user, but, if faithfully used, they will get their reward in the removal of the wart without leaving any scar.

(6564) J. S. S.: It is impossible to obtain Moree signals with a Thomson siphon recorder.

Any book on telegraphy will give you a description of the Atlantic cable.

(6565) G. G. M. writes: 1. I have made my own sine sticks, and would like to know the easiest and best way to amalgamate them? A. Dip them in dilute sulphuric acid, then sprinkle on a little mercury and rub it around, or dip the rods in a solution of nitrate of mercury. 2. Would like to know the ratio of the differ-ent ingredients for the solution of a bichromate of pot-ash battery? A. To a saturated solution of bichromate of potash, showly add non-fifth the pulls of suphyrics acid of potash, slowly add one-fifth its bulk of sulphuric acid. A I have some electric light carbon sticks (without cop-per) inch in diameter and 7 inches long. How many carbon sticks to zinc surface is necessary in a bisulphate of mercury battery; and give the solution for this bator mercury battery; and give the solution for this bat-lery. How many carbon sticks in a bichromate of pot-sah? A. Six or 8 carbon rods. Make a thick paste of bisulphate of mercury in water. 4. Give the best and casiest way of connecting the carbon eticks without soldering? A. Cast lead caps on the carbons. 5. In the answer to query No. 68.03, September 1, 1994, must the solution, when placed in the jar, be a thin paste or have some water added? A. Thin paste. 6. What is the best battery for induction coils? A. Grenet. 7. Does it matter whether or not the secondary is wound in Does it matter whether or not the secondary is wound in Defecator, L. A. Roussel.

Does it matter whether or not the secondary is wound in Defecator, L. A. Roussel.

Does it matter whether or not the secondary is wound in Defecator, L. A. Roussel.

Does it matter whether or not the secondary is wound in Defecator, L. A. Roussel.

Does it matter whether or not the secondary is wound in Defecator, L. A. Roussel.

Does it matter whether or not the secondary is wound in Defecator, L. A. Roussel.

Does it matter whether or not the secondary is wound in Defecator, L. A. Roussel.

Does it matter whether or not the secondary is wound in Defecator, L. A. Roussel.

Does it matter whether or not the secondary is wound in Defecator, L. A. Roussel.

Does it matter whether or not the secondary is wound in Defecator, L. A. Roussel.

Does it matter whether or not the secondary is wound in Defecator, L. A. Roussel.

Does it matter whether or not the secondary is wound in Defecator, L. A. Roussel.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether or not the secondary is wound in Defecator.

Does it matter whether whether

Deska adjustable support for school, G. A. Bobrito of quantity of primary to secondary for any number of wire, especially for Nos. 16 and 36? A. It depends on the ladneed current desired, 500 to 1,000 to 1. 9. What is the best material to use between primary and secondary wire in an induction coil? A. A glass tube, a rubber tube, or writing paper coated with shellar, varnish, or parafflu.

(6566) H. W. N. Says: Where can I find descriptions of automobile vehicles for use on common roads? A. See the Scientific for use on common ary 14, 21, 1891; May 21, 1892; February 3, March 31, April 21, June 23, 1894; January 13, February 3, March 23, April 5, May 4, June 8, 1896; and the Scientific Australia. Scientific Australia Supplemental Scientific Scientif

TO INVENTORS.

An experience of nearly fifty years, and the preparation of more than one bundred thousand applications for national and the subsets of the patent laws of the United States and all foreign countries may be had on application, and persons contemplating the securing of patents, either at home or abroad, are invited to write to this office for prices, which are low, in accordance with the times and our extensive facilities for conducting the business. Address MUNN & CO., office SCIENTIFIC AMERICAN, 361 Broadway, New York.

INDEX OF INVENTIONS

For which Letters Patent of the United States were Granted

June 25, 1895,

AND BACH BEARING THAT DATE

[See note at end of list about copies of these patents.]
Acid and by-products, method of and apparatus for manufacturing sulphuric, J. D. Daving
Advertising device, J. W. Snoddy
Annealing apparatus, gold, W. D. Porter
Basket, L. Bennett
Bearing, anti-friction, W. E. Shoemaker. 541,57 Bed bracket, G. Harris. 541,37 Bedstead, adjustable, L. W. Bickle. 541,38 Beer cooler trough, J. F. Duffy. Bevel, miter, and square, combined, A. J. Walker 541,51
Bicycle, J. A. Mundy
Bicycle lamp bracket, W. N. Beardstey. 51,200 Bicycle support and mud guard, 'combined, E. J. Klinck. St. See Adjustable bit. 54,700 Bit. See Adjustable bit.
Block. See Building block. Fuse block. Boat. See Folding boat. Boiler. See Hot water boiler. Steam boiler. Boiler cleaning device, D. O. Smith. Soiler beater, kitchen. A. Heller
Bicycle frame, E. M. Graham Bicycle jamp bracket, W. N. Beardsley 561,500 Bicycle support and mud guard, combined, E. J. Klinck
Bottle, A. A. Freeman. 541,758 Bottle stopper, F. A. Maquet. 541,658 Box. See Match box. Box lid and support therefor, C. G. Bennett. 541,568 Brake. See Bleycle brake.
Brick machine, re-press, J. A. Frey Brush for applying sensitizing solutions, E. A. Onee. Brush, metallic, A. Hankey Brush, metallic, A. Hankey Brush, tooth, J. W. Dennis, Brush, tooth, J. W. Dennis, Brush, tooney. 51,427
Oass. 41.776 Brush metallic, A. Hankey 54.575 Brush, tooth, J. W. Dennis. 54.1,775 Buckle, W. Looney. 54.1,875 Buckle, back band, F. C. Ruffhead. 54.1,875 Bullding block, J. Lee, Sr. 54.1,875 Bullding block, J. Lee, Sr. 54.1,875 Bullding block, J. Lee, Sr. 54.1,875 Bung and bushing, J. P. Baumgartner. 54.1,875 Burner. See Vapor burner. 54.1,775 Burner. See Vapor burner. 54.1,775 Burner, C. Haffeke. 54.1,875 Button shield, collar, J. A. Dunning. 54.1,785 Callpera, G. Harris. 54.1,786 Can filling machine, J. W. Kales. 54.1,786 Can opener, G. D. Hunsing. 54.1,506 Can burner, G. Harris. 54.1,786 Can opener, G. D. Hunsing. 54.1,506 Can burner, G. B. Harris. 54.1,506 Can burner, W. F. Richards. 54.1,506 Car burner, W. F. Richards. 54.2,507
Burner, C. Hafteke. 641.888 Button shield, collar, J. A. Dunning. 541.898 Calipera, G. Harris. 541.788 Can filling machine, J. W. Kales. 541,788 Can opener, G. D. Munstag. 541.898
Car coupling, J. G. Parrott 511.748 Car coupling, J. C. Parrott 541.468
Car fender, F. W. Darling 541,726 Car fender, I. Macowaky 441,770 Car fender, G. W. Maban 541,771 Car fender and snow cleener, C. A. Smith 541,737 Car, postal, H. H. Nessions 541,736 Car stop, G. H. Dippo 541,736 Cars, automatic life-guard for, C. M. Beebe 541,636
Car stop, G. H. Dippo. Cars, automatic life-guard for, C. M. Beebe
case. Castings, manufacturing steel, S. P. Hutchinson. 541,812 Chair. See Dental chair. Check book, A. W. Laughin
H. G. See Cotton chopper. Cistern forming device, J. A. Hartsell
Clevis, W. S. West
H. Hilborn. 541,548 Closet, W. Krebs. 511,486 Clonure, Guilleaume & Goldstein. 541,745 Clothes line clamp, J. H. Szyder. 441,599 Clutch and speed regulator, finid controlled, J.
Clutch, friction, M. O. Reeves
Combination lock C. F. Raymond
Hunt & King. 641.614 Cooker, food, Apple & Breitwiser. 641.705 Cooking, trouling, etc., apparatus for, C. Haffeke. 541.536 Cooking utensit, R. Gibbons. 541.705 Copying manifold sheet or book, carbon, E. J. Perry. 641.636
Condenser, F. M. w Decer Conveyer buckets, apparatus for filling endiess, I and & Kins. Eunt & Eunt
Crusher. See Ore crusher. Current motor, alternating, B. Bickemeyer
Damper, stovepipe, Farnell & Hoefer. Daylight in dark rooms, stores, stee, device for furnishing and distributing, B. Westermayr. 511.582 Defecator, L. A. Roussel

	Electric conductors, protector casing for underground, J. A. Kingdon. Electric motor, F. E. Herdman. Electric motor, W. J. Still.	541 500
n	Electric motor, F. E. Herdman	541.544
	Electric motor, W. J. Still. Blectric switch, W. P. Hancock	541,608
0	Electrical heater, thermo-controlled, L. E. Cus-	541,794
3-		
A	Riectrolytical process and apparatus, C. T. J.	541,467
18	Vautin. Elevator, J. H. Richards	541,663
100	Elevator apparatus, electric, F. B. Perkins	541,465 541,683 541,497 541,616 541,790
2	Vautin. Elevator, J. H. Richards. Elevator apparatus, electric, F. B. Porkins. Elevator attachment, E. C. Jenkins. Elevator attachment, 8. M. Philbrick. Elevators, device for removins resistances in starting electric, G. H. Whittingham. Engine. See Gas ongine. Richary steam ongine.	
16	starting electric, G. H. Whittingham	541,798
-	Steam engine.	E41 500
	Engraving machine table, C. C. Bruckner Envelope cord fastener, M. Scougale	541,523 541,602 541,666
P	Envelope machine counter, H. B. Cooley et al Envelope machines, drying chain for, H. B.	
3	Envelope making machine, H. B. Cooley et al	541,655 541,470 541,707
,	Evaporating pan, W. S. Balleu	
	Engine. See Gas engine. Rotary steam engine. Steam engine. Engraving machine table, C. C. Bruckner. Envelope cord fastener, M. Scourale. Envelope machines, drying chain for, H. B. Cooley et al. Envelope machines, drying chain for, H. B. Cooley et al. Evaporating pan, W. S. Ballou. Evaporating pan, W. S. Ballou. Fabric. See Double-faced fabric. Fence stay, wire, C. E. Little. Freader. See Car fender. Fither, J. W. Jarrett. Firearm sight, W. Lyman. 541.M6 to	541,487
	Pendes R. vie C. B. Letter. Frender, J. W. Jarrett. Frienru sight, v. Lender. Frienru sight, v. Lender. Frankru sight, v. Lender. Frietton means for producing instantaneous, R. J. Blume. Frankru sight, v. Lender. Fursting, machine for debairing, C. Schirmer. Furnace. See Blast furnace. Koasting furnace. Furnace, J. S. Dougherty.	541,755 541,560 541,547 541,789 541,464 541,766 541,778
	Fire extinguisher automatic, N. Hicks	541,547
	Fishing line drying reel, E. C. Vom Hofe	541,464
	Folding boat. J. H. Rushton	541,778
	Friction, means for producing instantaneous, K.	541,712 541,652
	Fur skins, machine for debairing, C. Schirmer	541,600
1	Furnace. See Blast furnace. Roasting furnace.	541,000
	Furniture, adjustable support for, G. A. Bebrick.	541,658 541,478
	Gas, apparatus for manufacture of, L. M. Heery	541,600 541,658 541,478 541,570 541,778 541,449 541,738
Ŋ	Gas lighter, automatic electric, Jaskey & Else	541,449
9	Fur skins, machine for debairing, C. Schirmer. Furnace, See Blast furnace. Koasting furnace. Furnace, J. S. Dougherty. Furniture, adjustable support for, G. A. Bobrick. Fuse block, Davis & Scott. Gas, apparatus for manufacture of, L. M. Houry. Gas engine, F. S. Mead. Gas lighter, automatic electric, J. L. Crevelling. Gas meters, apparatus for use in connection with, Gas or of burner heater. Gillham & West. Gas, process of and apparatus for manufacture of, E. N. Dickerson. Gas producer, S. R. Smythe. Gas regulator, R. V. Schoommaker. Gate, H. R. Kinser.	
8	Gas or off burner heater, Gillham & West	541,740 541,780
1	of, E. N. Dickerson	541,526
	Gas producer, S. R. Smythe	541,526 541,640 541,688 541,761 541,579 541,718
740956	Gate, Steffenson & Christensen	541,761
98	Gear, changeable driving, D. G. Bolton	541,718
900	Gold and silver, extracting, J. J. Crooke	641,658
	Gas producer, S. H. Smythe. Gas regulator, R. V. Schoommaker. Gate, H. R. Kinser. Gate, B. Gate, Stefenson & Christenson. Gear, changeable driving, D. G. Boiton. Generator. See Steam generator. Gold and silver, extracting, J. J. Crooke. Gold and silver from their ores, process of and apparatus for extracting, J. J. Crooke. Grader, road, J. Heuermann. Graim and straw separator, centrifugal, L. W. Macomber.	541,687 541,546
ő	Grader, road, J. Heuermann. Grain and straw separator, centrifugal, L. W. Macomber. Grain drill, A. Stansel. Graver and bandle, R. S. Peabody. Grinding and facing or polishing machine, S. Du Perow. Grinding machine, cutlery boister, A. Johnston. Gum feeding device, automatic, H. B. Cooley et al. Hamme fastener, J. N. Goodall. Hammer, steam, J. F. Doolittle.	
0 4	Grain drill, A. Stansel	541,769 541,697 541,673
4	Graver and handle, R. S. Peabody	
8	Perow	541,001 541,517
ĝ	Gum feeding device, automatic, H. B. Cooley	
8	Hame fastener, J. N. Goodall	541.741
0	Harness, J. Lewis	541,785 541,682 541,671
	Harvester, corn. J. E. Mazelin	541,562
t	Harvester, corn, M. Young	511,520
MA N	Gas or oil burner beater. Husting apparatus, C. W. Hunt	541,613
48	Hook. See Check book. Whiffletree book.	541,596
ě	Horsemen, combination tool for, J. C. F. Schenck	541,798 541,649
4	Horseshoe fastening, E. T. Coveli	541,524
	Gum feeding device, automatic, H. B. Cooley et al. Hammer, steam, J. F. Doolittle. Harmes, J. Lewis. Harmes, J. Lewis. Harmes, J. Lewis. Harvester, corn, H. E. Marsiin. Harvester, corn, M. Toung. Heater. See Boiler beater. Electrical beater. Gas or oil burner beater. Histoin apparatus. C. W. Hunt. Hook. See Check book. Whiffietree book. Horse blanket, J. Hand. Horremen, combination tool for, J. C. F. Schenck Horseboe bars, manufacture of, W. D. Young. Hornesboe fasteoing, E. T. Coveli. Hose coupling, W. Curlett. Hose compliag. C. Callaban.	541,716
0		541,620
4	Insulator and fuse holder, combined, Scott &	561,556
5	Davis. Jacquard mechanism for weaving double-faced rabrics. W. Weaver.	541,450
8	Jar cover fastening, R. Naegeli	541,048 541,775
9	Knife or fork blanks, machine for rolling, A. Johnston	541,618
78	Labeling machine bottle & Slegel	541,618 541,575 541,460 541,512
775	Lamp, electric arc, A. W. Smith	-
5	Temps one concreting hymnes for W.P. Cmith	541,541
ŷ	Lamps, gas generating burner for, H. F. Smith. Lamps, repairing incandescent, J. Mohrle. Lantern, gas arc, G. F. Kleum. Leather aktwing and splitting machine, J. R.	541,541 541,508 541,491 541,619
300	Leather skiving and splitting machine, J. R.	541,001
ğ	Scott. Light. See Electric arc light. Lines, instrument for making broken, J. H. Knight.	
		orrions
ĕ	Knight	541,568
3998898	Knight. Lock. See Combination lock. Door lock. Permutation lock. Pin lock.	541,588
699668	Knight. Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Locu Jacquard mechanism, W. Weaver	541,588
	Knight. Look. See Combination look. Door look. Permutation look. Pin look. Look and latch, combined. J. H. Barrett. Loom Jacquard mechanism, W. Weaver	541,568 541,601 541,646 541,581
	Knight. Look. See Combination look. Door look. Permutation look. Pin look. Look and latch, combined J. H. Barrett. Loom Jacquard mechanism, W. Weaver. Loom shuttle actuating mechanism, W. Weaver. Looms, take-up mechanism for siat and wire fabric, L. Mollart. Magnet. electro. F. B. Corey.	541,568 541,601 541,646 541,581
	Knight. Look. See Combination look. Door look. Permutation look. Pin look. Look and latch, combined J. H. Barrett. Loom Jacquard mechanism, W. Weaver. Loom shuttle actuating mechanism, W. Weaver. Looms, take-up mechanism for sist and wire fabric, L. Mollart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove. Match box and cigar cutter. Towasend & Comway.	541,568 541,601 541,646 541,581
	Angle. Angle. Lock. See Combination lock. Door lock. Per- Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism, W. Weaver	541,568 541,666 541,561
	Anight. Lock. See Combination lock. Door lock. Per- Lock. See Combination lock. Door lock. Per- Lock and latch combined. J. H. Barrett. Lock and latch combined. J. H. Weaver. Loom stated puscenting mechanism. W. Weaver. Looms, take-up mechanism for sist and wire fabric. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer. T. F. Grove. Match making machine, L. H. Montross. Measure, registering lumber. G. Krueger. Metal stripe to cardoord, etc., machine for fast- Metal stripe to cardoord, etc., machine for fast-	541,558 541,666 541,561 541,563 541,471 561,482 541,703 541,564 541,703
	Lines, instruments for making broken, J. H. Asight. Lock. See Combination lock. Door lock. Per- Lock and to be combined. H. Barrett. Lock and to be combined. H. Barrett. Lock and to be combined. H. Barrett. Lock and the combined. H. Weaver. Looms, take-up mechanism for sist and wire fabric, L. Moliart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove. Match making machine, L. H. Montross. Measure, registering lumber, G. Krueger. Motal stripe to cardoord, etc., machine for fastening, Saltstorn & Nicolai. Moler for measuring liquids, C. W. Beck.	541,568 541,666 541,561
	Lines, instruments for making broken, J. H. Kaight. Loek. See Combination lock. Door lock. Permutation lock. Fin lock. Loek. See Combination lock. Boor lock. Permutation lock. Fin lock. Loom state of the lock of the lock. Loom state of the lock of the lock of the lock. Loom state of mechanism, W. Weaver. Looms, take-up mechanism for sint and wire fabric, L. Moliart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove. Match box and cigar cutter, Townsend & Conway. Match making machine, L. H. Montross. Measure, registering lumber, G. Krueger. Motal stripe to cardboard, etc., machine for fastening, Saltzkorn & Nicolai. Mester for measuring liquids, C. W. Beck. Moistening gum on stamps or envelopes, machine for, M. Cole.	541,558 541,801 541,646 541,561 541,763 541,702 541,703 541,703 541,680 541,523
	Lines, instruments for making broken, J. H. Kaight. Lock. See Combination lock. Door lock. Permutation lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacobuard mechanism. W. Weaver511,614, Looms, take-up mechanism for sint and wire fabric, L. Mollart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove Mail bag catcher and deliverer, T. F. Grove Match box and cigar cutter, Townsend & Conway. Match making machine, L. H. Montross. Measure, registering lumber, G. Krueger. Motal stripe to cardboard, etc., machine for fastening, Saltzkorn & Nicolal. Meter for measuring liquids, C. W. Beck. Moistening gum on stamps or envelopes, machine for, W. R. Cole Mop wringer, A. M. Burnham. Motion to morable objects, self-neutralizing fiext-	541,558 541,666 541,561 541,563 541,471 561,482 541,703 541,564 541,703
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver. Looms take-up mechanism for sist and wire fabric, L. Mollart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove. Match box and cigar cutter, Townsend & Comway. Match making machine, L. H. Montross. Measure, registering lumber, G. Krueger. Metal stripe to cardboard, etc., machine for fastening, Baltzkorn & Nicolai. Meter for measuring liquids, C. W. Beck. Molstenner gum on stamps or envelopes, machine for, W. R. Cole. Mop wringer, A. M. Burnham. Mothon to movable objects, self-neutralixing flexible conductor for transmitting, B. W. War-	541,558 541,801 541,646 541,561 541,763 541,702 541,703 541,703 541,680 541,523
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver. Looms take-up mechanism for sist and wire fabric, L. Mollart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove. Match box and cigar cutter, Townsend & Comway. Match making machine, L. H. Montross. Measure, registering lumber, G. Krueger. Metal stripe to cardboard, etc., machine for fastening, Baltzkorn & Nicolai. Meter for measuring liquids, C. W. Beck. Molstenner gum on stamps or envelopes, machine for, W. R. Cole. Mop wringer, A. M. Burnham. Mothon to movable objects, self-neutralixing flexible conductor for transmitting, B. W. War-	541,558 541,803 541,646 541,583 541,471 541,482 541,703 541,703 541,680 541,503 541,503 541,503
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver. Looms take-up mechanism for sist and wire fabric, L. Mollart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove. Match box and cigar cutter, Townsend & Comway. Match making machine, L. H. Montross. Measure, registering lumber, G. Krueger. Metal stripe to cardboard, etc., machine for fastening, Baltzkorn & Nicolai. Meter for measuring liquids, C. W. Beck. Molstenner gum on stamps or envelopes, machine for, W. R. Cole. Mop wringer, A. M. Burnham. Mothon to movable objects, self-neutralixing flexible conductor for transmitting, B. W. War-	541,568 541,646 541,561 541,563 541,471 541,563 541,703 541,703 541,503 541,503 541,503 541,503 541,503
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver. Looms take-up mechanism for sist and wire fabric, L. Mollart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove. Match box and cigar cutter, Townsend & Comway. Match making machine, L. H. Montross. Measure, registering lumber, G. Krueger. Metal stripe to cardboard, etc., machine for fastening, Baltzkorn & Nicolai. Meter for measuring liquids, C. W. Beck. Molstenner gum on stamps or envelopes, machine for, W. R. Cole. Mop wringer, A. M. Burnham. Mothon to movable objects, self-neutralixing flexible conductor for transmitting, B. W. War-	541,568 541,646 541,541 541,471 541,471 541,471 541,472 541,703 541,703 541,503 541,503 541,503 541,503 541,503 541,503 541,503
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver. Looms take-up mechanism for sist and wire fabric, L. Mollart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove. Match box and cigar cutter, Townsend & Comway. Match making machine, L. H. Montross. Measure, registering lumber, G. Krueger. Metal stripe to cardboard, etc., machine for fastening, Baltzkorn & Nicolai. Meter for measuring liquids, C. W. Beck. Molstenner gum on stamps or envelopes, machine for, W. R. Cole. Mop wringer, A. M. Burnham. Mothon to movable objects, self-neutralixing flexible conductor for transmitting, B. W. War-	541,553 541,665 541,561 541,563 541,763 541,763 541,763 541,763 541,763 541,564 541,563 541,563 541,563 541,563 541,563 541,563 541,503 541,516
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver. J. H. Gartel. Loom Jacquard mechanism, W. Weaver. J. H. Gartel. Looms Lake-up mechanism for slat and wire fabric, L. Mollart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove. Mail making machine, L. H. Montross. Measure, registering lumber, G. Krueser. Motal stripe to cardooard, etc., machine for fastening, Baitskorn & Nicolai. Moter for measuring liquids, C. W. Beck. Moistening gum on stamps or envelopes, machine for, W. R. Cole. Mop wringer, A. M. Burnham. Motion to movable objects, self-neutralixing flexible conductor for transmitting, B. W. Warwick. Motors, electrical controller for, O. H. & A. F. Freper. Motors, electrical controller for, O. H. & A. F. Freper. Music book leaf holder, C. Barns. Music planting machine, C. W. Gildden Mail machine, wire, A. Rosa.	541,553 541,645 541,541 541,563 541,763 541,763 541,763 541,763 541,564 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver	541,553 541,645 541,541 541,563 541,763 541,763 541,763 541,763 541,564 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver	541,553 541,645 541,541 541,563 541,763 541,763 541,763 541,763 541,564 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,563
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver	541,523 541,603 541,603 541,561 541,563 541,563 541,763 541,763 541,763 541,763 541,603 541,603 541,603 541,603 541,603 541,603 541,603 541,603 541,603 541,603
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver	541,523 541,603 541,603 541,561 541,563 541,563 541,763 541,763 541,763 541,763 541,603 541,603 541,603 541,603 541,603 541,603 541,603 541,603 541,603 541,603
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver	541,563 541,861 541,861 541,861 541,861 541,861 541,661 541,661 541,662 541,562 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,663 541
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver	541,563 541,861 541,861 541,861 541,861 541,862 541,462 541,762 541,762 541,762 541,762 541,762 541,563 541,563 541,563 541,563 541,563 541,563 541,663 541
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver	541,563 541,861 541,861 541,861 541,861 541,861 541,661 541,661 541,662 541,562 541,563 541,563 541,563 541,563 541,563 541,563 541,563 541,663 541
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver. Looms lake-up mechanism for sint and wire fabric, L. Mollart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove. Match stript to cardooard, etc. machine for fastening, Baltskorn & Nicolai Motal stript to cardooard, etc. machine for fastening, Baltskorn & Nicolai Moter for measuring liquids, C. W. Beck. Mojstening gum on stamps or envelopes, machine for, W. R. Cole. Mop wringer, A. M. Burnham Motion to movable objects, self-neutralizing ffexi- ble conductor for transmitting, B. W. War- wick. Motor. See Current motor. Electric motor. We motor. Move motor. Move motor. Move motor. Move motor. Move motor. Move motor. Music, clip or classify for holding sheets of, J. Hood. Mail assorting machine, C. W. Gildden Mail assorting machine, C. W. Gildden Music, clip or classify for holding sheets of, J. Hood. Mill machine, wire, A. Rosa. Niter cake or other acid sulphates, utilising, J. D. Darling. Mut lock, J. H. Ramsom, J. Mut lock, J. C. Fleming. Mut lock, J. C. Fleming. Mut lock, J. C. Fleming, J. Selwig Mut lock, J. Selwig,	541,563 541,861 541,861 541,861 541,861 541,862 541,462 541,762 541,762 541,762 541,762 541,762 541,563 541,563 541,563 541,563 541,563 541,563 541,663 541
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver. Looms lake-up mechanism for slat and wire fabric, L. Mollart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove. Measure, registering lumber, G. Krmeser. Metal stript to cardooard, etc., machine for fastening, Baltskorn & Nicolai. Motal stript to cardooard, etc., machine for fastening, Baltskorn & Nicolai. Moter for measuring liquids, C. W. Beck. Mojstening gum on stamps or envelopes, machine for, W. R. Cole. Mop wringer, A. M. Burnham. Motion to movable objects, self-neutralizing fexible conductor for transmitting, B. W. Warwick. Motor, Esc Current motor. Electric motor. Motors, electronal controller for, O. H. & A. F. Frieper Motors, electronal controller for, O. H. & A. F. Frieper and the form of the form of the fact of the form of the fact of	541,523 541,801 541,861 541,561 541,561 541,471 541,472 541,501 541,702 541,502 541,503 541
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver	541,563 541,861 541,561 541,561 541,561 541,471 541,472 541,57
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver	541,523 541,801 541,861 541,561 541,561 541,471 541,472 541,501 541,702 541,502 541,503 541
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver	541,523 541,801 541,861 541,561 541,561 541,471 541,472 541,501 541,502 541,502 541,503 541
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver	541,523 541,801 541,861 541,561 541,561 541,471 541,472 541,501 541,502 541,502 541,503 541
	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism, W. Weaver. Looms take-up mechanism for slat and wire fabric, L. Mollart. Mannet, electron and deliverer, T. F. Greve. Match box and cigar cutter, Townsend & Conway. Motal stripe to cardboard, etc., machine for fastening, Saltzkorn & Nicolal. Moter for measuring liquids, C. W. Beck. Moistening gum on stamps or envelopes, machine for, W. K. Cole. Mop wringer, A. M. Burnham. Motors, electrical cojects, self-neutralising fext- ble conductor for transmitting, B. W. War- wick. Motors, electrical controller for, O. H. & A. F. Feeper. Music book leaf holder, C. Barns. Music, clip or clamp for holding sheets of, J. Hood. Music book leaf holder, C. Barns. Music, clip or clamp for holding sheets of, J. Hood. Mile assorting machine, C. W. Glidden Mile assorting washer, C. A. Bartiff. Oli and gas, simultaneously transmitting, J. J. Suckert. Prometer & Thompson. Paper box blanks, machine for making, C. E. Clement. Paper tagers or wicks, machine for making, C. E. Clement. Paper tagers or wicks, machine for making, C. E. Permutation lock, F. D. Sweet. Paper tagers or wicks, machine for making, C. E. Permutation lock, F. D. Sweet. Paper tagers or wicks, machine for making, C. E. Permutation lock, F. D. Sweet. Physical colors of the proper design. P	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541
68601754850	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism. W. Weaver. Looms lake-up mechanism for slat and wire fabric, L. Mollart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove. Matcher and Controller (Groverer) Measure, registering lumber, G. Krmeser. Metal stript to cardooard, etc. machine for fastening, Baltskorn & Nicolai Meter for measuring liquids, C. W. Beck. Mojstening gum on stamps or envelopes, machine for, W. R. Cole. Mop wringer, A. M. Burnham. Motion to movable objects, self-neutralizing ffexi- ble conductor for transmitting, B. W. War- wick. Motor. See Current motor. Electric motor. Motors, become controller for, O. H. & A. F. Fepper motor. Motors, controller for, O. H. & A. F. Fepper motor. Music, clip or classify for holding sheets of, J. Hood. Mail assorting machine, C. W. Glidden. Mail machine, wire, A. Rosa. Niter cake or other acid sulphates, utilizing, J. D. Darling. Music, J. C. Fleming. Music, J. C. Fleming, Music, J. C. Fleming, Music, See Evaporating pan. Packare, smild, O. S. Follows. Das See Evaporating pan. Packare, smilot, S. Follows. Das See Evaporating pan. Paper box blanks, machine for making, C. E. Clement. Photographic printing frame, C. R. Schilling. Pin. See Sarety pin. Pin. See Sarety pin. Pin. Deck, J. J. Ridgway. Pipe coupling, hard and soft metal, S. M. Friede. Septement. Pipe coupling, hard and soft metal, S. M. Friede. Septement.	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541
68601754850	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined, J. H. Barrett. Lock and latch, combined, J. H. Barrett. Loom Jacquard mechanism. W. Weaver. Looms lake-up mechanism for slat and wire fabric, L. Mollart. Magnet, electro, F. B. Corey. Mail bag catcher and deliverer, T. F. Grove. Matcher and Controller (Groverer) Measure, registering lumber, G. Krmeser. Metal stript to cardooard, etc. machine for fastening, Baltskorn & Nicolai Meter for measuring liquids, C. W. Beck. Mojstening gum on stamps or envelopes, machine for, W. R. Cole. Mop wringer, A. M. Burnham. Motion to movable objects, self-neutralizing ffexi- ble conductor for transmitting, B. W. War- wick. Motor. See Current motor. Electric motor. Motors, become controller for, O. H. & A. F. Fepper motor. Motors, controller for, O. H. & A. F. Fepper motor. Music, clip or classify for holding sheets of, J. Hood. Mail assorting machine, C. W. Glidden. Mail machine, wire, A. Rosa. Niter cake or other acid sulphates, utilizing, J. D. Darling. Music, J. C. Fleming. Music, J. C. Fleming, Music, J. C. Fleming, Music, See Evaporating pan. Packare, smild, O. S. Follows. Das See Evaporating pan. Packare, smilot, S. Follows. Das See Evaporating pan. Paper box blanks, machine for making, C. E. Clement. Photographic printing frame, C. R. Schilling. Pin. See Sarety pin. Pin. See Sarety pin. Pin. Deck, J. J. Ridgway. Pipe coupling, hard and soft metal, S. M. Friede. Septement. Pipe coupling, hard and soft metal, S. M. Friede. Septement.	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541
686017548650	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism. W. Weaver	541,523 541,801 541,861 541,561 541,561 541,471 541,472 541,562 541
686017548650	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism. W. Weaver	541,523 541,801 541,801 541,801 541,801 541,801 541,801 541,802 541,802 541,802 541,802 541,802 541,802 541,803 541,80
686017546650 3 4 2	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism. W. Weaver	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541
686017546650 3 4 2	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism. W. Weaver	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541
686017546650 3 4 2	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism. W. Weaver	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541
686017546650 3 4 2	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism. W. Weaver	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541
686017546650 3 4 2	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism. W. Weaver	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541
686017546650 3 4 2	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism. W. Weaver	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541
686017546650 3 4 2	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism. W. Weaver	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541
686017546650 3 4 2	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism. W. Weaver	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541
686017546650 3 4 2	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism. W. Weaver	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541
686017546650 3 4 2	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism. W. Weaver	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541
686017546650 3 4 2	Lock. See Combination lock. Door lock. Permutation lock. Pin lock. Lock and latch, combined. J. H. Barrett. Lock and latch, combined. J. H. Barrett. Loom Jacquard mechanism. W. Weaver	541,523 541,801 541,561 541,561 541,561 541,561 541,562 541

Railway switch, A. B. Milliass	541,007
Gullmann. Rheostat for starting electric motors, automatic-	541,588
Guilmann theostat for starting electric motors, automatic working, F. E. Herdman. 501,502 Bivesting machine, cardboard, Salizkorn & Nicolat Riveting machines, adjustable table for, F. 4. Cuenot.	541,548 541,791
Rolling shears, L. C. Thompson	541,525 541,718 541,468
Rope clamp A W Lowin	541,551 541,557
Ruber boot or shoe, C. L. Higgins	541,684 541,610 541,708
Safaty pin E B Too	541,782 541,765 541,798
CHEN DESCRIPTION OF THE PARTY AND ASSESSED.	541,521 541,810 541,808
Sash support and lock, W. W. Dwigans. Scraper, C. E. Burbank. Screen, G. W. Cross. Seam for sowed articles, H. H. Fefel. Seams, method of and tool for forming about	541,595 541,478
metal, A. Langlais Separator. See Grain and straw separator. Sewing machine, J. T. Colitus	661,621
metal, A. Langlais. Separator. See Grain and straw separator. Sewing machine, J. T. Collina. Sewing machine, H. H. Fefel. Sewing machine, H. C. Peters. Sewing machine, T. Kundts.	561,479 561,479
Sewing machine cabinet, T. Kundtz Sewing machine cabinet, Kundts & Kosch	541,555 541,554
Sewing machine drop stand, Diehl & Kraemer Sewing machine feeding mechanism, T. McGowan	541,567 541,567
Sewing machine looper, R. G. Woodward	541,518 541,492
Sewing marbine, H. H. Fefel. Sewing machine, H. C. Peters. Sewing machine cabinet. T. Kundts. Sewing machine cabinet. Rundts & Kosch. Sewing machine droinet. Rundts & Kosch. Sewing machine feeding mechaniza, T. McGowan Sewing machine feeding mechaniza, T. McGowan Sewing machine predict foot. L. Muther. Sewing machine needle guard. L. Muther. Shaft aligning device, J. M. Ingrig. Shears. See Rolling abears. Sheat metal articles, apparatus for forming, C. E. Richardson.	541.754
Sheet metal articles, apparatus for forming, C. H. Richardson.	541,455
Sheet metal working machine, U. D. Alexander Shell for high explosives, J. E. Bott	561,500 541,588 551,781
Show case, J. H. Hohmann	541,638
Signaling device, code, W. Rymer	541,672 541,505
extracting, J. Crooks	541,659 541,569
Snow melting machine, S. Bestty	541,569 541,709 541,766
Soda water dispensing apparatus, I. D. Pearson Spectacle case, G. H. Lloyd	541,777 541,767 541,581
Spike pulling implement, Graves & Knight Spring. See Wagon platform apring.	541,715
Stand. See Display stand.	541,687
Steam engine, F. G. Hobart	541,685
Steam, generating, G. G. de Villeneuve	541,379 541,589
Stone, tile, plaster, etc., compound for making ar- tificial, H. S. Utley	541,818
sheara. See Rolling abear. sheat metal articles, apparatus for forming, C. B. Richardnon. Richardnon. Sheet metal working machine, U. D. Alexansier. Shell for high explosives, J. E. Bott. Show case, J. H. Hohmann. Sifter, ash, G. Shanklin. Sirn, advertising, J. P. Pappit. Sirnaling device, code, W. Rymer. Silver from its ores, process of and apparatus for extracting, J. J. Crooks. Sirup can for dispensing fouritains, I. D. Pearson. Sirup can for dispensing fouritains, I. D. Pearson. Snow plow, rotary, F. D. Linton. Sod a water dispensing apparatus, J. D. Pearson. Spectacle case, G. H. Lioyd. Spike pulling implement, Graves & Knight. Spring. See Waron platform apring. Spring wheel, I. M. Bourke. Stand. See Display stand. Steam engine, C. A. Wright Steam engine, C. A. Wright Steam generating, G. G. ovideneuve. Steam generating, G. G. ovideneuve. Steam generating, G. G. ovideneuve. Stopper, See Bottle stopper, Fine stopper, Stopper, See Bottle stopper, Fine stopper, Stovepipe elbows, machine for making ar- Stovepipe elbows, machine for making crimped, G. Cunin.	541,744
G. Cunin	541,472
Sugar making, L. Wulf	541,778 541,799 541,786
Suspenders, E. H. Benners	841,529 841,710 541,681
G. Cunin. Structure, portable, L. Nolan. Sugar making, L. Wulff. Sugar mill shredding attachment, C. Dube. Suppository mould, D. Genese. Suspenders, E. H. Benners. Suspenders, Bracing, H. Puts. Switch. See Electric switch. Railway switch. Syringe buib, H. D. Smith. Tallow and meat extracts, etc., process of and ap-	541,000
paratos for arteaciton of M. I. Domingov	541.599
Tongs, C. Bulmer	541,690
Top, C. Barus Track clearing apparatus, A. E. Trevithick Trolley fender, J. P. Taylor	541,502 541,500 541,796
Tub. See Bath tub.	
Tube corrugating machine, B. Hall. Tug, thill, Carr & Washer. Tug, thill, W. F. Sweet.	541,700
Tuning pin, H. Muller. Twine holder, E. J. Powers.	541,624
Type distributing machine, I. K. Johnson Valve, cut-off, F. Markgraf	\$61,758 \$41,772
Valve, engine, H. R. Fay	541,752
Vapor burner, T. A. Camplon	M1.717
Vehicle seat, W. F. Downey Vehicle wheel, E. D. Wasseil	841,601 541,516
Vessels, apparatus for raising sunkes, H. Schon. Vulcanizing apparatus, Sine & Ward	541,794
Tub. See Bath tub. Tube corrugating machine, B. Hall. Tug, thill, Carr & Washer Tug, thill, W. F. & Weet. Tuning pin, H. Muller Twine holder, E. J. Fowers. Type distributing machine, I. E. Johnson. Valve, motor, A. Horne Valve, mulified safety, Hasicharst & Cole. Vapor burner, raw procosa; C. Goergan. Vohicle seat, W. F. Downey. Vohicle wheel, E. D. Wassell. Voscels, apparatus for raising sunkas, H. Schon. Volcanizing apparatus, Sine & Ward. Wasdon platform spring, C. A. Weed. Washer, See Nut locking washer. Washing machine, I. B. Pettit. Watch, stem winding and setting, Matheson & Water closet connection, W. JJ. Weels. Waster closet connection, W. JJ. Weels.	541.677
Watch, stem winding and setting, Matheson &	E41 501
	1007'007
Water main equalizer, D. O'Donneil	541,647 541,816
Water closet connection, W. II. Weish. Water main equalizer, D. O'Donneil. Wave motor, F. O. Busling. Wheel. See Spring wheel. Vehicle wheel. Whiffletree hook. H. P. Essale.	541,647 541,816 541,681
Wave motor, F. O. Rusling. Wheel. See Spring wheel. Vehicle wheel. Whiffletree hook, H. P. Egedal. Wicking, etc., machine for making covered, T.	541,681 541,751
Wave motor, F. O. Rusling. Wheel. See Spring wheel. Vehicle wheel. Whiffletree hook, H. P. Egedal. Wicking, etc., machine for making covered, T.	541,681 541,751
Ware motor, F. O. Rusling." Wheel. See Spring wheel. Vehicle wheel. Whithetree hook, H. P. Egiedal. Wicking, etc., machine for making covered, T. McGowan. Window, B. F. Retts. Wrench, A. Muller.	541,681 541,751
Wave motor, F. O. Rusling. Wheel. See Spring wheel. Vehicle wheel. Whiffletree hook, H. P. Egedal. Wicking, etc., machine for making covered, T.	541,681 541,751
Wave motor, F. O. Rusling. Wheel. See Spring wheel. Vehicle wheel. Whiffletree hook, H. P. Egedal. Wicking, etc., machine for making covered, T.	541,681 541,751

DESIGNS.	
Hose coupling, D. S. Robinson	,438 ,439 ,427 ,434 ,418 ,426 ,429
Lamp fount holder, J. E. Bohner. 24 Lever, J. Macphail 24 Miter piece, E. A. Langenbach 26	428
Money obange stand, E. A. Verbeck 24, Plateau frame, P. F. Schaefer. 24, Spoon, J. W. Mtalllot 38, Spoon, I. B. Smith 24, Table top frame, J. E. Bohner 24, 33, 24, 12, 2	423 421 417
Table top frame, J. R. Bohner. 24,423, 24, 70 becoping the P. B. Jackson. 24. Vending machine case. Wick. lamp, J. S. Donohee. 24. Woven fabrie, J. B. Morgan. 34,400, 34,400	419 426 437

TRADE MARKS.
Beer, lager, National Union of the United Brewery
Workmen. 26,128 Boots and shoes, N. L. Millard & Company. 26,721
Carpets, rugs, floor cloth, and oil cloth, James
Humphries & Sons. 26,72 Carts, trucks, and runners, hand, F. J. Aubeuf. 26,74
Essences of peppermint, wintergreen, and anise, and flavoring extracts, Red Seal Remedy Com-
pany
pany. 98.784 Grinding wheels or tools, O. A. Hensel. 98.784 Gum, chewing, Faultiess Chemical Company. 28.736
Harness renovating preparations, D. Hayes 20,780 Inks and fluids, writing, C. L. Lochman
Liniment, arnica, Van Vicet Mansfield Drug Com-
Medicinal purposes, chemical compounds for, F.
won Heyden Nachfolger
troubles, liquid, L. F. Freytag & Company 26,730
Medicine to cure tobacco babit and chronic consti- pation, Sterling Remedy Company. 28,729
Oil dressing for wood floors, S. B. Brewster. 36,738
Remodies, certain named, E. Alexander. 98,731 Soap, laundry, D. Rupp. 95,739 Tobacco, plug, Whiteman-McNamara Tobacco
Tobacco, plug, Whiteman-McNamara Tobacco Company
Company
Yarna, W. Morris & Sons
Yarns, J. Paton, Son & Company
A printed carr of the appointment of drawing of

A printed copy of the specification and drawing of up patent in the foregoing list, or any patent in print sued since 185%, will be furnished from this office for cents. In ordering pieces tate the name and sumber the patent desired, and remit to Mann & Co., 2sl roadway Now York.

Canadian patents may now be obtained by the in-entors for any of the inventions named in the fore-ong list, provided they are simple, at a cast of \$80 each, if complicated the rost will be a little more. For full natructions address Munn & Co., 381 frandway, New fork. Other foreign patents may also be obtained.

Modvertisements.

ORDINARY RATES.

fuside Page, each insertion - - 25 cours a line linea Page, each insertion - - - \$1.00 a line

The above are charres per again line—about eight order per line. This notice above the width of the line to large type. Sharravine may head adversements at the same rate per again line, by measure ent, as the lotter person. Advertisements must be ceived at Publication Office as carry as Thursday cordinate appear to the following week's line.



Star * Serew cutting athes Cross Feed 9 and 12 inch Swing.

New Designs. Novel Features. Send for Chialogue B. SENECA FALLS MFG. COMPANY, 605 Water St., Seneca Falis, M. Y.

LATHES. Shapers, Pinners, Drilla, Machine Shop Outflie, Foot Lathes, Tools and Supplies. Catalogue From. SEBASTIAN LATHE CO., IB CILLWITT ST., CINCINVATI, O.

FOOT POWER LATHES



For Electrical and Experimental Wark Gunemiths and Yorl Makers General Machine Shop Work Bicycle Repair Work

THE BEST FOOT POWER LATHES MADE. PREE

W. F. & JOHN BARNES CO.

1999 RUBY STREET, ROCKFORD, ILLS.

AMERICAN PATENTS. -- AN INTER-



SAMUEL HALL'S SON, 229 West 10th St., New York. SUPERIOR TO COTTON WASTE

If you want the best Lathe and Drill



NOW READY I

Seventeenth Edition of

Experimental Science



REVISED AND ENLARGED.

198 Pages and 110 Superb Cuts added.

Just the thing for a boilday present for any man, reman, stadent, teacher, or any me interested in effence. In the new matter contained in the last edition will be cound the Scientific Use of the Phonograph, the curious pical illusion known as the Anorthoscope, together rith other new and interesting Optical Hissions, the priceil Frojection of Oraque Objecta. New experiments if Projection, Iridescent Guses, some points in Photomaphy, including Hand Camerus, Cane Cameras, etc.; ystems of Electrical Distribution, Ricetrical Ore Find-, Ricetrical Racker, Electric Chizet, How to Color antern Slides, Budy of the Stars, and a great deal of the content of the stady of the Stars, and a great deal of the content of the stady of the Stars, and a great deal of the content of the stady of the Stars, and a great deal of the content of the stady of the Stars, and a great deal of the content of the stady of the Stars, and a great deal of the content of the stars and a great deal of the content of the stars and a great deal of the content of the stars and a great deal of the stars.

MUNN & CO., Publishers.
Office of the SCIENTIFIC AMERICAN,
361 BEGADWAY, NEW YORK.

ELECTRICITY

IMPROVED SPEED INDICATOR.



BUSINESS MEN

The value of the SCIENTIFIC AMERICAN as an medium cannot be overestimated. Its circulary times greater than that of any similar jour is many times greater than that or any similar journal now published. It goes into all the States and Territories, and is read in all the principal libraries and reading rooms of the world. A business man wants something more than to see his advertisement in a printed newspaper. He wants circulation. This he has when he advertises in the SCIENTIFIC AMERICAN. And do not let version in the SCIENTIFIC AMERICAN. And do not the advertising agent influence you to substitute so other paper for the SCIENTIFIC AMERICAN when a lecting a list of publications in which you decide it is your interest to advertise. This is frequently done a the reason that the agent gets a arger commission fro the papers having a small circulation than is allowed. the SCIENTIFIC AMERICAN.

dress MUNN & CO., Publishers, 361 Broadway, New York.

"WOLVERINE" GAS AND GASOLINE ENGINES, STATISHARY. The "Wolverine" is the only re-versible Marine Gas Engine on the market, It is the lightest en-gine for its power. Requires no-linced engineer. About

WOLVERINE MOTOR WORKS, ORAND RAPIDS, MICH. BALL BEARING AXLES AND RUB-



Manufactory Established 1761.

LEAD PENCILS, COLORED PENCILS, SLATE
PENCILS, WRITING SLATES, STEEL PENS, GOLD
PENS, INES, PENCIL CASES IN SILVER AND IN
GOLD, STATIONERS' RUBBER GOODS, RULERS,
COLORS AND ARTISTS' MATERIALS.

78 Respin Street

78 Reade Street, - - - New York, N. Y. Manufactory Established 1761.

"Climax" Stereotyper Moulding Press combined,

or making perfect Cellulaid Steventynes to be used in place of metal tereotypes. Also for making Ruber Stamps. Should be in use in ver Stamps. Should be in use in version of the State St. Ast., lec. 36, 188. Send for directors to

Dec. 30, 1830. Send for circular to
THE J. F. W. DORMAN CO.
217 E. German St., Baltimere, Md.
Manufacturers of
Rubber Stamps, Vulcanizers, Stereotype Machinery and Supplies.

TELEPHONES

are good—not "cheap things," The dist n cost is little. We guarantee our apparatus at ntee our customers against loss by patent sail marantee and instruments are ROTH GOOD. WESTERN TELEPHONE CONSTRUCTION CO.,

46 Monadnock Block, Cuicago. st Manufacturers of Telephones in the United States

SINTZ GAS ENGINE CO. GRAND RAPIDS, MICH.,

Manufacturers of the Sintz Sta-tionary and Marine Gas and Gasoline Engines. Especially adapted for Bouts and Electric Liebting. Runs with manufac-tured or natural gas—Boats and hunce are an expectation of all. If Sond for Catalogue. Monition this paper.

HELLO, CENTRAL!



ARTESIAN WELLS—BY PROF. E. G. Smith. A paper on artesian wells as a source of water supply. Essential reclouded conditions of artesian wells. Some observed features of artesian well apply. Contained in SCHENTIFIC ANSIGNA SUPPLEMENT. No. 943. Price 10 cents. To be had at this office and from all newdeniers.

Pumping Water by Compressed Air. We take pleasure in amnouncing that by arrangements made with J. G. Pohle, we are enabled to furnish our customers with the

POHLE AIR LIFT PUMP. rotected by numerous American and Foreign patents. This department of our business will be under the per-onal supervision of Dr. Poblé, the inventor and pat'ee THE INGERSOLL-SERGEANT DRILL CO. Havemayer Building, M Cortlandt St., New York

ROCK DRILLS (\$PACE) AIR COMPRESSORS & MINING. TUNNELING.

ELECTRICITY AND PLANT GROW-ing.—A paper by Prof. i... H. Balley, of Cornell Univer-sity, describing and giving the results of a series of ex-periments upon the effect of electrical illumination upon the growth of plants. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 990 and 991. Price II cents each. To be had at this office and from all news-

RAND DRILL Co 23 PARK PLACE



MERICAN GAS FURNACE CO. CHEAP AND PERFECT FUEL GAS. GAS BLAST FURNACES,

HIGH PRESSURE BLOWERS, ETC. SO NASSAU STREET. NEW YORK.

KOBERT POOLE & SON CO. ENCINEERS & MACHINISTS. TRANSMISSION MACHINERY MACHINE MOULDED CEARING SPECIAL FACILITIES FOR THE HEAVIEST CLASS OF WORK


SCIENTIFIC AMERICAN DYNAMO. CIENTIFIC AMERICAN DYNAMU, secreption of a plain shunt-wound dynamo of a simple onstruction, capable of supplying a current of from 00 is 100-you incandescent lamps, or of being used as a b. p. motor. This machine was constructed especially or the benefit of the readers of the Scientific American, Mr. W. S. Bishop, of New Haven, Com. It is degreed to meet the wants of mechanics and amateurs be desire to construct a simple dynamo for their own be, but who do not care to enter into the subject extendically. With Millustrations. Contained in **INNTIFIC MUSICAL CONTROLLED IN SUPPLEMENTATION OF THE STRUCTURE OF THE

BALTIMORE, MD.

CLARK'S PATENTED Rotary Upholstery Brush.



FRANKLIN S. MILES A SE



tained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 979. Price 10 cents. To be had at this office and from all newsdesiers.



BELTING of Various Styles, ELEVATORS, CONVEYORS, Chain 4 COAL MINING and HANDLING MACHINERY. The JEFFREY MANUFACTURING CO., COLUMBUS, O.





How To Make a Dynamo OR MOTOR. A horse power size, illustrated will fall working drawings. By Edw. Trevert. Price Mo. Bubier Publishing Co., Lynn, Mass

They All Like It. The Ladies Like It. So Do The Men. Children Enjoy It.

Layman Pneumatic Boats.

EF See Sci. Am., May 18, 1965.

Send 4c. in stamps for our handsomely illustrated catalogue. Address H. D. LAYMAN, 851 Broadway, New York.



- - THE - -



The Most Pepular Scientific Paper in the World Only \$3.00 a Year, Including Postage.

Weekly-52 Numbers a Year.

This widely circulated and splendidly illustrated paper is published weekly. Every number contains sixteem pages of useful information and a large number of original engravings of new inventions and discoveries, representing Engineering Works, Steam Machinery, New Inventions, Novelities in Machanies, Manufactures, Chemistry, Electricity, Telectraphy, Photography, Architecture, Agriculture, Horticulture, Natural History, etc. Complete list of Patents each week.

Terms of Subscription.—One copy of the SCIENTIFIC AMERICAN will be sent for one year—Be numbers—postage prepaid, to any subscriber in the United States, Canada, or Mexico, on receipt of Three Bollars by the publishers; six months, \$1.00. Clubs.—Special rates for several names, and to Postmasters. Write for particulars.

The affect way to remit is by Postal Order, Draft, or Express Money Order. Money carefully placed inside of envelopes, securely sealed, and correctly addressed, soldom goes astray, but is at the sender's risk. Address all letters and make all orders, drafts, etc., payable to MILIN & CO., 361 Herondway, New York. Weekly--52 Numbers a Year.

letters and make all orders, drafts, etc., payable to MUNN & CO., 361 Broadway, New York.

Scientific American Supplement

This is a separate and distinct publication from The SCIENTIFIC AMERICAN. Dut is uniform therewith in size, every number containing sixteen large pages full of engravings, many of which are taken from foreign papers and accompanied with translated descriptions. The SCIENTIFIC AMERICAN SUPPLEMENT is published weekly, and includes a very wide range of contents. It presents the most recent papers by eminent writers in all the principal departments of Science and the Useful Arts, embracing Biology, Geology, Mineralogy, Natural History, Geography, Archesology, Astronomy, Chemistry, Electricity, Light, Heat, Mechanical Engineering, Steam and Railway Encineering, Mining, Ship Building, Marine Engineering, Photography, Technology, Mannfacturing Industries, Sanitary Engineering, Agriculture, Horticulture, Domestic Economy, Hography, Medicine, etc. A vast amount of fresh and valuable information obtainable in no other publication.

The most important Engineering Works, Mechanisms, and Manufactures at home and abroad are illustrated and described in the Supplement.

Price for the Supplement, for the United States, Canada, and Maxico, \$4.00 a year: or one copy of the Supplement.

Scientific American and one copy of the Supplement, both mailed for one year to one address for \$7.00. Single copies, Mccents. Address and remit by postal order, express money order, or check,

MUNN & CO., 361 Broadway, New York.

MUNN & CO., 361 Broadway, New York.

Building Edition.

THE SCHNTIFIC AMERICAN BUILDING EDITION is issued monthly. \$2.50 a year. Single copies, \$5 conts. Thirty-two large quarto pages, forming a large and splendid Massatise of Architecture, richly adorned with elegant plates and other fine engravings; illustrating the most interesting examples of modern Architectural Construction and allied subjects.

A special feature is the presentation is each number of a variety of the latest and best plans for private residences, city and country, including those of very moderate cost as well as the more expensive. Drawings in perspective and in color are given, together with Floor Plans, Descriptions, Locations, Butimusted Cost, etc.

The elegance and cheapness of this magnificent work have won for it the Largest Circulation of any Architectural publication in the world. Sold by all newsdealers. \$2.50 a year. Remit to

mun & Co., 361 Broadway, New York.

Export Edition

of the SCIENTIFIC AMERICAN, with which is incorporated "La AMERICA CIENTIFICA E INDUSTRIAL," or Spanish edition of the SCIENTIFIC AMERICAN is published monthly, and is uniform in size and typography with the SCIENTIFIC AMERICAN. Every number contains about 50 pages, profusely illustrated. It is the finest scientific, industrial export paper published. It circulates throughout Cuba, the West Indies, Mexico, Central and South America, Spain and Spanish possessions—wherever the Spanish inguage is spoken. THE SCIENTIFIC AMERICAN EXPORT EDITION has a large guaranteed circulation in all commercial places throughout the sevid. 500 a year, postpaid, to any part of the world. Single copies, 25 cents.

ET Manufacturers and others who desire to secure foreign trade may have large and handsomely displayed announcements published in this edition at a very moderate cost. Bates upon application.

MUNN & CO., Publishers.

361 Broadway, New York.

HENRY CAREY BAIRD & CO.

SILVERIAL PUBLISHERS, BOOKSELLERS & IMPORTERS
S16 Walnut St., Philadelphia, Pa., U. S., A.
Let Our New and Revised Catalogue of Practical and
clentific Books, 90 pages, 8vo, and our other Catalogue
and Circulars, the whole covering every branch of Scioce applied to the Arts, sent free and free of postage
coe applied to the Arts, sent free and free of postage
any one in any part of the world who will furnish his

The Scientific American Reference Book.

A most useful little bound book of 150 pages, comprising, probably, the most extensive variety of standard, practicula, condensed information ever furnished to the public for so small a price, only 25 cents.

Among its contents are. The Last Census of the United States (1300), by States, Territories, and Counties: Table of Cities having over 5,000 inhabitants: Map of the United States — miniature Sutlins; The Patent Laws (full text): The Principal Mochanical Movements—illustrated by 150 small diagrams—of value to inventors and designers of machanism: Medallion Portraits of Distinguished American Inventors Valuable Tables relating to Steam, Bleetricity, Heat, Metals, Weights, and Measures.

Sent by mail to any address on receipt of price

MUNN & CO., Publishers 361 Broadway, New York.

by water companies everywhere. Address for circular Hackus Water Motor Co., Newark, N. J., U.S.A.

'DIETZ" TUBULAR DRIVING LAMP



light.
IT throws all the light straight ahead from 300 to 300 feet.

F Send for Book.

E. Dietz Co.

7 Laight Street,
New York.



SEND for Catalogue of the Musical Instru-ment you think of buying. Violins repaired by the Cremona System. C. STORY, S Central St., Boston, Mass.

FASTER THAN SHORTHAND



A Valuable Book



12,500 Receipts. 708 Pages. Price \$5.

Bound in Sheep, \$6. Half-Morocco, \$6.50.

This splendid work contains a careful compilation of the most useful Receipts and Replies given in the Notes and Queries of correspondents as published in the Scientific American durint the past fifty years; together with many valuable and important additions.

Over Tweive Thousand selected Receipts are there collected; nearly every branch of the useful arts being represented. It is by far the most comprehensive foliame of the kind ever placed before the public. The work may be regarded as the product of the stud-es and practical experience of the ablest chemists and orders in all parts of the world; the information given being of the highest walte, arranged and condensed in oncine form convenient for ready use.

Almost every inquiry that can be thought of, relating to formule used in the various manufacturing indus-tries, will here be found answered.

Instructions for working many different processes in the arts are given.

hose who are engaged in any branch of industry bably will find in this book much that is of practical ne in their respective callings.

Those who are in search of independent business employment, relating to the home manufacture of an the articles, will find in it hundreds of most excellent

Send for Descriptive Circular, MUNN & CO., Publishers,

SCIENTIFIC AMERICAN OFFICE. 361 Broadway, New Y



GAS ENGINE CASTINGS
also for Water Motor, Dynamo, Botler, Engine, etc.
A. F. WEED & Co., 106 Liberty St., N. Y.

VERY LATEST NOVELTY.

Little Giant Drilling Machine

WITH STRAIGHT TABLE.
Furnished also with swinging table
Arranged for both Hand and Power.
Drills from 1/4 to 1/4 inch bole.
Drills to center of 1/4 inch circle.
Table perfectly square with spindle and pustures of 1/4 inches.
Freed has a run of 4 inches.
Freed has a run of 4 inches.
WELLS BROS. & CO.,
P. O. Box B, Greenfield, Mass.

THE MICROGRAPH

Fastest Grinders known. Can grind anything NO PICKING.
Made Sharp. Stay Sharp
Will Fit any Mill Frame.
Cheap as Best French Buhrs.

de of Large Blocks of Emery Set in Metal.

Sturtevant Mill Go., Boston Mass. MILLSTONES.



The Typewriter EXCHANGE,

11 Barclay St., New York We will save you from 10 to 50 per cent. on Typewriters of all makes.

Send for catalogue.

BI-SULPHIDE for use in the arts, Killing Insects in Graids, Killing Burrowing An-OF CARBON E. H. TAYLOH, Cleveland. Ohio



For catalogue, address the Chancellor.
W. J. HOLLAND ALLEGHENY PA.

ICE MACHINES. Corlies Engines. Brewers' and Buttlers' Machinery. THE VILTER Mrg. Co., 80 Clinton Street, Milwaukee, Wis.



ICE HOUSES. — DESCRIPTION OF the houses as they were built a century ago. Contained in Scientific American Supplement, No. 933. Price 18 cents. To be had at this office and from all newsdealers.

MONITOR VAPOR ENGINE AND POWER COMPANY,

We manufacture Tents of every variety and size, for all conceivable purposes.

We have been in the business for fifty-four years and know bow to main themproperty.

We have male Tents for the Wal, Department of the U. 8. Government for many years.


We are now justify the lowest prices ever heard of, owing to the low frice of coutoft can be added to the low frice of coutoft can be with the coutoft years of the coutoft of the said Caup first large of the coutoft of the said Caup first large of the coutoft of the said Caup first large of the coutoft of the said Caup first large, it you are lightnessed, along receipts of your seconds.


GEO. B. CARPENTER & CO.

RACINE BOAT MEG C PACHTS
RACINE WIS U.S.A.
DESIGNES AND BUILDERS ROY BOM
PRESSAND WORN CHARACTER
CANCES

CHICAGO

202-208 So. Water St.,







Experimental & Model Work E. V. BAILLARD, 100 Liberty Street, N. Y.



The Berkefeld House Filter mly Kitter Removing Tuphoid and Cholera Bacilli, tested and indorsed by many leading authorities in Europe and Am-erica. It gives a continuous flow of fil-tered water, a half out of y free from germs. It is easily cleaned, as all im-purities remain on the surface of the filtering cylindes, Cylinders can be ster-llised by boiling in water for one hour. Send for circulary and prices to the BERKEFELD FILTER CO., 4 Cedar Street, New York

ACETYLENE, THE COMMERCIAL Synthesis of illuminating Hydrocarbons—A paper by Prof. Vivian B. Lewes, read before the London Society of Aria. The production of acetylene from calicic arbide obtained by means of the electric furnace, the light-giving value of this ydrocarbon by yolkstone, the light-giving value of this ydrocarbon by yolkstone, and its commercial possibilities. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, NO. 4998. Price 18 cents. To be had at this office and from all newsdesiers.



MONEY MADE AT HOME.

ast month I cleared, after paying all expenses, \$255.58, in month before \$185.68, and have at the same time at-ded to my regular business. I believe anyone, anyere, can do as well, as I have not a particularly good atton and not much experience. When you have an icle that every family wants, it is very easy selling it seems strange that a good, cheap dish washer was rer before placed on the market. With the Perfocal and the placed on the market, with the Perfocal and the placed on the market with the perfocal and the placed on the market with the perfocal and the placed on the perfocal and the placed on the perfocal and the per





I.

THE DENSMORE-

THE WORLD'S GREATEST TYPEWRITER."

"DOING A LAND OFFICE BUSINESS " We have just received (April, 1893), on competition, a written order for DENSTORES for the Government Land Offices throughout the United States.

WE CHALLENGE any other Typewriter company to show so large a order from a customer for a single delivery.

rincive Pamphiet and Telling To miajs sent Free.

DENSMORE TYPEWRITER CO., 316 Broadway, New York



Transmitters, Receivers, Magneto Bells, Cords and Parts of Telephones.

MIANUS ELECTRIC CO.,

REPAIR BICYCLES FOR A LIVING GOOD LIVE Bellows, Blownipe, Vise, Files, Spoke Threader, Solder Borax, Spoke Wire. Full outsite for factories. 12 Send 5 2-cent stamps for Illus, Cate logue of Tools. FRASES CO., 21 Warren St., New York.

CALENDOLIS TYPESETTING MAa machine re-cilian Domini or to compuse



NewYork NORWICH LINE The AIR LINE LIMITED New York and Boston.

Parson's Horological Institute. School for Watchmakers

ENGRAVERS AND JEWELERS.

ed for Catalogue and Referes

PARSON'S HOROLOGICAL INSTITUTE, 302 Bradley Avenue, PEORIA. ILL.



Engineers and Firemen Send 20. stamp for 3 taning a list of questions saked by a board of examining engineers. Strunibers Pub. Co., St. Louis, Mc.



Agents Wanted.
Sanitary Sonp Vase Co.,
Aqueduct Bidg., BOCHESTER, N. Y.





Architectural Books

Useful, Beautiful and Cheap.

Any person about to erect a dwelling house or eta-ble, either in the country or city, or any builder wishing to examine the latest and best plans for a church, school house, club house, or any other public building of high or low cost, should procure a complete set of the ARCHITECTS AND BUILDERS EDITION of the SCI-ENTIFIC AMERICAN. ENTIFIC AMERICAN.

The information these volumes contain renders the work almost indispensable to the architect and builder, and persons about to build for themselves will find the work suggestive and most useful. They contain draw-

work suggestree and most useful. They contain drawings in perspective and in s.ior, together with floor
plans, costs, location of residence, etc.

Two volumes are published innually. Volumes 1 to
18, which include all the na__bers of this work from
commencement to December. 1884, may now be obtained
at this office or from Bookseilers and Newsdealers.

Price, stitched in paper \$2.00 per volume. These volumes contain all the plates and all the other interesting
matter participates to heave. matter pertaining to the work. They are of great per-manent value. Forwarded to any address. MUNN & CO., Publishers, 361 Broadway, New York.

THE HYPNOSCOPE for physiciane, dentists, in the occult, proves hypnotisation possible in all cases. 28 the occult, proves hypnotisation possible in all cases, page book on hypnotism, etc., \$2. 10) page pampilet. NATOMAL LEUT., \$21 Spring St., \$7., Los Angeles,

Movertisements.

ORDINARY RATES.

fuelde Page, each insertion. - 75 cents a line flack Page, each insertion. - 81.00 a line

The above are charges per again line—about a bries per line. This notion shows the width of the all is set in again type. Begravings may head at semests at the mane rate per again line, by mea-ner, as the letter press. Advertisements mus-porived at Publication Office as early as Thur round to appear in the following week's issue.





. BOILER CLEANER . COMPOUND

We Boo't Offer Grainities, but our Circular will give you the information that will enable you to Save Time, Trouble and Money, Tried, operation, and he made you have the fact. Butturess on the Bast.

Kemble Bidg., 19 Whitehalf St., R.Y.

WE ARE BUILDING . . . The Celebrated-

The De La Vergne Refrigerating Machine Co.

FOOT E. 138TH STREET, NEW YORK.

\$18 buye a beautiful little Cance; or \$125

DO YOU WANT A LAUNCH?

That you can run yourself.



That requires

neither Licensed Engineer nor Pilot.

THE ONLY NAPHTHA LAUNCH.

GAS ENGINE AND POWER COMPANY, 185th St., Morris Heights, New York City.



"Brownie" Bicycle Lock.

Malled on receipt of 40c. G. A. SUPPLEE & CO., 265 N. 9th St., PHILA.


THE BICYCLE: ITS INFLUENCE IN with and Disease.—By G. M. Hammond, M.D. A val-oblet and interesting paper in which the subject is ex-setively treated from the following standpoints: 1. e use of the cycle by persons in health. 2. The use of cycle by persons diseased. Contained in SCIENTFIC AMERICAN SUPPLEMENT, No. 1 602. Price D cents. To be had at this office and from all newsjeniers.



GENTS WANTED FOR FINE TOOLS IN EVERYSHI CH.BESLY& CO. THE "TRENTON" CYCLOMETERS







Only Perfect Pulverizer of all Refractory Substances.

Will work either wet or dry, and deliver a finished product. Capacity, 3 to 4 tons per hour on Phosphate Rock; 1 1/2 to 2 tons per hour on Portland Cement, Quartz, or Ores, depending on hardness of material to be pulverized and fineness of product. Grinds from 30 to 250 Mesh with equal facility.

MATERIAL. BINNINGS POWER PRODUCTS STATISTICS ASSOCIATELY GLAS-ANTEED IN EVERY RESPECT, BOTH AS TO CONSTRUCTION AND CAPACITY. PIRST COST, WEAR, AND DEFRATION EXPENSE MUCH LESS THAN STAMP NILLS. LASSE NUMBER OF MILLS IN USE ON CHE-PERSON MATERIALS BYTH POSITIVE SUCCESS IN SYEST INSTANCE.

BRADLEY PULVERIZER CO., 92 STATE STREET. BOSTON.

The American Bell Telephone Company,

125 Milk Street, Boston, Mass.

This Company owns Letters-Patent No. 463,569, granted to Emile Berliner November 17, 1891, for a combined Telegraph and Telephone, covering all forms of Microphone Transmitters or contact Telephones.

to \$100.00.

lightest and most practical cameras for hand pod use. An illustrated manual, free with Kodak, tells how to develop and print the

Eastman Kodak Company,
Rechester,
N. Y. Send for Catalouge.



Computing Figures mentally is probably the hardest kind of toil known. The Comptometer makes it casy, is twice as quick, insures accuracy and relieves all mental and nervon strain. Why don't you get one?

FELT & TARRANT MFG CO.

ELECTRO MOTOR, SIMPLE, HOW TO our to make a motor which higher he driven the higher by a current derived from a batter, and would have sufficient power to operate a feet or any machine requiring not over one man power. If figures, Contained in SCIANTERE LABORITA. No. 464; Proc. 10 can't be be had at these and from all new allesting.

Premo Gameras



Are perfect in construction, workmanship and finish, and contain more modern im-provements than any other Camera. We make several styles and guarantee them all

ROCHESTER OPTICAL CO.

JESSOP'S STEEL HEYES



Three New Model

HAVE YOU EXAMINED THEM?

Address THE SMITH PREMIER TYPEWRITER COMPANY, Syracuse, N. Y., U.S. A.

ENGINES, Boilers and Machine Tools.

EMERY, sincry Wheels, Grinding Ma-Quick process and Grinders' Supplies, Buy of THE TANITE Cts., New York Crry, CINCIRNAT, and STROUDERSUNG, FA.

Patented Novelties Manufactured.



CIDER & WINE PRESS
MACHINERY.
POWER AND HAND PRESSES.
(Copacity, 10 to 130 Ebbs. in ten hours.)
Bend for 50-page Catalogue.
Empire State Pulley and Press Co.
FULYON, ORWEGO CO., N. Y.

CHONORORORORORORO \$1-Pocket Camera-\$

CHILD CAN OPERATE IT

Booklet on receipt of sta or Photoret, with institions, on receipt of \$1. Mazine with films for 36 azine with films for a put-tures, age, extra. Sample photo free if you mention this paper. Agents Wanted. Satisfaction or money rejusted. MAGIC INTRODUCTION CO., 371 Breadway, new York.,

Cacacacacacacaca

ICE-HOUSE AND COLD ROOM,—BY B. G. Hatfield, With directions for construction. Four ongravings. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 59. Price 10 cents. To be had at this office and from all newschelers



MOEH. P. THE Motor of 19th Century ECONOMY RELIABILITY. P. O. BOX 163. Sterling. III

THE M. & B. TELEPHONE.

Absolutely Non-infringing.
Absolutely Guaranteed.
Absolutely the Best Exchange
SWITCH BOARDS.
Illustrated Catalogue on application Free.
. 187 Aposts Wooted.
THE U.S. TELEPHONE CONSTRUCTION CO.
181-130 S. Fourth St., PHILADELPHIA.



Always ready for use at any speed or pressure.

This instrument received a special diploma at the World's Exposition, Chicago, 198, for Convenience, Ricchasical Construction, and Accuracy under all pressure. Ex Catalogue Reent upon application THOMPSON & BUSHNELL CO., 112 Liberty St., New York

PRIESTMAN SAFETY OIL ENGINE

Reconcunical, Simple, Safe, Au-tomatic. For Electric Light-ing, Pumping, Milling, etc. PRIESTMAN & COMPANY, inc. Front and Tnaker Street

STERLING CYCLE WORKS,
236-240 Carroll Ave., D 1, CHICAGO.



COMPOSITION AND CONSTITUTION of Cartain Alloya.—A paper by Dr. C. R. Aider Wright, F. R. S., onlowning the author's experimental inquiries into the subject of the relations of metals to one another as regards their manual miscibility or solubility when rendered fluid by heat. With one illustration. Contained in SCIENTIPIC AMERICAN SUPPLEMENT, Nos. 999 and 1000. Price 10 cents each. To be had at this office and from all newsdealers.

Towers, Tanks and Tubs

PATENT SECTIONAL ALL IRON TOWERS

ALL WOOD TOWERS. **ELEVATED TANKS**

W. E. CALDWELL CO., 219 E. Main Street,



PRINTING INKS.